



H12-261^{Q&As}

HCIE-Routing & Switching (Written) V3.0

Pass Huawei H12-261 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/h12-261.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

When DLDAP detects a unidirectional fiber link, Huawei devices perform the following operations by default: The DLDAP state machine changes to the Disable state; a trap is generated; the interface is automatically blocked.

- A. TRUE
- B. FALSE

Correct Answer: A

QUESTION 2

The following description of cross-domain features is correct vpn Option C?

- A. Reporting Forwarding Layer Labels Up to two are required in the script.
- B. ASBR VPNv4, VPNv4 does not save routes, and does not advertise between routes.
- C. VPN PE PE, the VPN route is exchanged between the ingress and the egress.
- D. Cross-domain mode is not suitable when using multiple VPN-Option-c ASs.

Correct Answer: BC

QUESTION 3

For Layer 2 VPN technology, the following is correct?

- A. VPLS is a widely used technology for the network. It can provide three-layer transparent layer reporting and multi-point access.
- B. VPLS BUM configuration complex high-complexity, two-network transparent layer transmission message
- C. BGP EVPN multi-homing supports leased isolation, and broadcast suppression
- D. BGP EVPN VPLS MAC solves the problem of address drift and multi-tenancy that cannot be supported.

Correct Answer: BCD

QUESTION 4

Which of the following statements regarding MP-BGP is false?

- A. The MP_UNREACH_NLRI attribute of Update packets does not contain path information
- B. MP_REACH_NLRI and MP_UNREACH_NLRI are optional transitive attributes
- C. The complete MP_REACH_NLRI attribute structure contains the address family, next hop, and prefix information



D. MP-BGP can be used to allocate labels

Correct Answer: B

QUESTION 5

On router HW1, you want to view the status of a frame relay connection. Which "display" commands will show the status of a Frame-Relay PVC? (Multiple choice)

- A. display frame relay interface
- B. display frame relay pvc
- C. display fr lmi-info
- D. display fr map-info interface Serial 0/0/0
- E. display fr interface Serial 0/0/0
- F. display fr inarp-info

Correct Answer: DE

[H12-261 PDF Dumps](#)

[H12-261 VCE Dumps](#)

[H12-261 Braindumps](#)