H31-211 Q&As

Huawei certified Network Associate - HCDA (Carrier IP)

Pass Huawei H31-211 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/h31-211.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

- **Instant Download** After Purchase
- **100% Money Back** Guarantee
- **365 Days** Free Update
- **800,000+** Satisfied Customers

QUESTION 1

In VRP, what are the following statements about RIP route aggregation?

A. RIP V1 supports route aggregation by default. You can disable route aggregation when needed.

B. RIP V2 supports off route aggregation.

C. RIP V1 does not support CIDR

D. RIP V2 supports subnet route aggregation

Correct Answer: BCD

QUESTION 2

The level of TCP/IP protocol is not divided according to the OSI reference model. Corresponding to OSI\\'s seven-layer network model, which of the following options is not defined?

A. Link layer and network layer

B. Network layer and transport layer

C. Session layer and presentation layer

D. Transport layer and session layer

Correct Answer: C

QUESTION 3

During the PPP negotiation process, if no response packet is received from the peer within the interval of the negotiation timeout, PPP will resend the previously sent packet. Such as Configure- Request. By default, how many seconds does the PPP negotiation timeout?

A. 1

B. 2

C. 3

D. 4

Correct Answer: C

QUESTION 4

Given a subnet address of 5.32.0.0 and a subnet mask of 255.224.0.0, what is the highest host address allowed in this subnet?

A. 5.32.255.254

B. 5.255.255.254

C. 5.63.255.254

D. 5.54.255.255

Correct Answer: C

QUESTION 5

When a router that enables proxy ARP receives an ARP request packet, it finds that the destination address of the packet is not its own. Which operation is required? (Multiple selection)

A. Discard the message

B. Find the route to the destination address

C. If there is a route to the destination address, send its own MAC address to the ARP requester.

D. Broadcast ARP request message

Correct Answer: BC

Latest H31-211 Dumps H31-211 VCE Dumps H31-211 Study Guide