



H31-211^{Q&As}

Huawei certified Network Associate - HCDA (Carrier IP)

Pass Huawei H31-211 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/h31-211.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Regarding VRRP, is the following statement correct?

- A. The master sends VRRP packets periodically. If the backup does not receive packets for a long time, the status is changed to Master.
- B. Backup sends VRRP packets periodically. If the master receives the packets from the backup, the master compares the priorities and determines whether the status is set to Master or Backup.
- C. If there are multiple backups, the election priority will be the new master according to the VRRP packets sent.
- D. In the backup fault-tolerant protocol, there is also an HSRP protocol. This protocol is identical except that the packet structure is different from VRRP.

Correct Answer: A

QUESTION 2

Which of the following network types are there?

In order to avoid the problem of slow route convergence, the DR and BDR router roles are designed.

(multiple choice)

- A. Point to point
- B. Broadcast type
- C. NBMA
- D. Point to more points

Correct Answer: BC

QUESTION 3

What are the TCI (Tag Control Information) fields in the VLAN tag? (Multiple choice)

- A. Priority
- B. CFI
- C. VLAN Identifier
- D. TPID

Correct Answer: ABC



QUESTION 4

In the frame relay network, what are the correct descriptions about the bandwidth control parameters?

(multiple choice)

- A. CIR is the rate of user information transmission agreed by the network and the user, that is, the committed information rate.
- B. Bc is the amount of data that the network allows users to transmit at CIR rate Tc intervals. They are related to $T_c = B_c / CIR$.
- C. Be is the amount of data that the network allows users to transmit more than Bc during the Tc interval.
- D. If the user transmits information at a rate less than or equal to CIR, the transmission of this part of information should be guaranteed.

Correct Answer: ABCD

QUESTION 5

The network administrator is removing multiple VLANs from the switch. When the administrator enters the undo vlan 1 command, he receives an error message.

What is the cause of the error message?

- A. VLAN can only be deleted by the user who created it
- B. VLAN 1 can be deleted only after the role of VLAN 1 is assigned to other VLANs.
- C. The command was not entered correctly, resulting in a syntax error
- D. VLAN 1 is the default management VLAN and cannot be deleted.

Correct Answer: D

[H31-211 PDF Dumps](#)

[H31-211 Study Guide](#)

[H31-211 Braindumps](#)