



H31-611^{Q&As}

HCNA - SDN(Huawei Certified Network Associate - SDN)

Pass Huawei H31-611 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/h31-611.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What kind of packet is used by BGP to transmit version number and AS number information?

- A. Open
- B. Update
- C. Keepalive
- D. Notification

Correct Answer: A

Reference: <http://www.ciscopress.com/articles/article.asp?p=2756480andseqNum=3>

QUESTION 2

Which statement about BGP is true?

- A. BGP is used in Ass or between Ass to transmit and control routing information.
- B. BGP is used in an AS to discover paths.
- C. BGP is directly carried in IP packets.
- D. BGP must establish peer relationships based on direct links.

Correct Answer: A

Reference: <https://support.huawei.com/enterprise/en/doc/EDOC1100058403/cf72786c/overview-of-bgp>

QUESTION 3

Which of the following statements are true about the meaning of the peer 20.1.1.2 allow-as-loop 2 command? (Choose all that apply.)

- A. The local AS number can be repeated in the AS_Path attribute in the received routes.
- B. 2 indicates the number of times the AS number can be repeated.
- C. This command can only be used on EBGp peers.
- D. By default, the number of times the AS number is allowed to be duplicated is 1.

Correct Answer: BD

Reference: <https://support.huawei.com/enterprise/en/doc/EDOC1100008283/14418f9d/peer-allow-as-loop>



QUESTION 4

Which of the following protocols is defined by the network layer of the OSI protocol suite?

- A. ES-ES
- B. RIP
- C. OSPF
- D. IS-IS

Correct Answer: D

QUESTION 5

Which of the following statements is true about proxy ARP?

- A. Proxy ARP allows a gateway directly connected to the host to use its own MAC address to reply to ARP requests in place of destination host.
- B. Proxy ARP allows a gateway directly connected to the host to help the destination host to transmit ARP packets across VLANs.
- C. Proxy ARP is used for communication within a VLAN.
- D. Proxy ARP means to buy the permission to use ARP packets from a proxy.

Correct Answer: A

Reference: <https://support.huawei.com/enterprise/en/doc/EDOC1000166635/620f63f3/proxy-arp>

[Latest H31-611 Dumps](#)

[H31-611 Practice Test](#)

[H31-611 Braindumps](#)