



HADOOP-PR000007^{Q&As}

Hortonworks Certified Apache Hadoop 2.0 Developer (Pig and Hive Developer)

Pass Hortonworks HADOOP-PR000007 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hadoop-pr000007.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hortonworks Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which two of the following statements are true about Pig's approach toward data? Choose 2 answers

- A. Accepts only data that has a key/value pair structure
- B. Accepts data whether it has metadata or not
- C. Accepts only data that is defined by metadata tables stored in a database
- D. Accepts tab-delimited text data only
- E. Accepts any data: structured or unstructured

Correct Answer: BE

QUESTION 2

Which one of the following Hive commands uses an HCatalog table named x?

- A. `SELECT * FROM x;`
- B. `SELECT x.-FROM org.apache.hcatalog.hive.HCatLoader(\\x\\);`
- C. `SELECT * FROM org.apache.hcatalog.hive.HCatLoader(\\x\\);`
- D. Hive commands cannot reference an HCatalog table

Correct Answer: C

QUESTION 3

Review the following data and Pig code:

```
M, 38, 95111
F, 29, 95060
F, 45, 95192
M, 62, 95102
F, 56, 95102
```

```
A = LOAD 'data' USING PigStorage(',')
AS (gender:chararray, age:int, zip:chararray);
```



What command to define B would produce the output (M,62,95102) when invoking the DUMP operator on B?

- A. B = FILTER A BY (zip = = \"95102\" AND gender = = M");
- B. B= FOREACH A BY (gender = = \"M\" AND zip = = \"95102\");
- C. B = JOIN A BY (gender = = \"M\" AND zip = = \"95102\");
- D. B= GROUP A BY (zip = = \"95102\" AND gender = = \"M\");

Correct Answer: A

QUESTION 4

You have the following key-value pairs as output from your Map task:

- (the, 1)
- (fox, 1)
- (faster, 1)
- (than, 1)
- (the, 1) (dog, 1)

How many keys will be passed to the Reducer's reduce method?

- A. Six
- B. Five
- C. Four
- D. Two
- E. One
- F. Three

Correct Answer: B

Explanation: Only one key value pair will be passed from the two (the, 1) key value pairs.

QUESTION 5

Which one of the following classes would a Pig command use to store data in a table defined in HCatalog?

- A. org.apache.hcatalog.pig.HCatOutputFormat
- B. org.apache.hcatalog.pig.HCatStorer
- C. No special class is needed for a Pig script to store data in an HCatalog table



D. Pig scripts cannot use an HCatalog table

Correct Answer: B

[Latest HADOOP-PR000007 Dumps](#)

[HADOOP-PR000007 Study Guide](#)

[HADOOP-PR000007 Braindumps](#)