



HCE-3700^{Q&As}

Hitachi Vantara Certified Expert - Performance architect

Pass Hitachi HCE-3700 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hce-3700.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You are recommending RAID 6 to a customer for a non-database HDT pool.

What are two reasons for this recommendation? (Choose two.)

- A. When capacity is pooled; the whole pool is affected when one parity group fails.
- B. RAID 6 provides the most efficient use of system processor resources.
- C. RAID 6 minimizes exposure to double disk failure.
- D. RAID 6 provides the optimum overall performance of all RAID types.

Correct Answer: BC

QUESTION 2

A user with a diskless VSP G800 uses ShadowImage from the G800 with a virtualized VSP G200 system. Application performance suffers during the frequent ShadowImage resynchronization operations.

What should be done to reduce the impact of the ShadowImage throughput in this scenario?

- A. Configure both sets of disks into an HDT pool and let the HDT scheme manage the different workloads.
- B. Define the ShadowImage target volumes to use dedicated external FC paths using dedicated RAID groups.
- C. Set Copy to 15.
- D. Increase the VSP G800 cache size to improve the application cache hit rates.

Correct Answer: A

QUESTION 3

Which two UNIX commands provide metrics about disk device I/O activity? (Choose two.)

- A. perfmon
- B. iogen
- C. iostat
- D. sar

Correct Answer: CD

QUESTION 4



You are designing a VSP G1000 solution for a customer and you need to determine the appropriate disk type and RAID level.

What information do you need to design the solution? (Choose three.)

- A. type of workloads
- B. workloads read-write ratio
- C. operating systems used in the environment
- D. fan-in and fan-out ratios
- E. expected I/O rates

Correct Answer: ABE

QUESTION 5

A VSP G1000 customer is concerned about high VSD utilization alerts during their nightly backup and application maintenance window. To address their concerns, you want to inform them about the maximum acceptable utilization level range.

What would be the range in this scenario?

- A. 30-40%
- B. 40-50%
- C. 50-60% D. 80% or higher

Correct Answer: D

[Latest HCE-3700 Dumps](#)

[HCE-3700 PDF Dumps](#)

[HCE-3700 VCE Dumps](#)