



HCE-3700^{Q&As}

Hitachi Vantara Certified Expert - Performance architect

Pass Hitachi HCE-3700 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hce-3700.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

For a VSP G1000 system serving a mission critical interactive workload, which two statements are true about VSD failover? (Choose two.)

- A. The VSD receiving the workload of a failed VSD is not pre-determined.
- B. Providing reserved capacity to accommodate failure is a requirement when planning for capacity for normal operations.
- C. The workload of a failed VSD board always transfers to its redundant partner VSD board.
- D. The workload of a failed VSD board is dynamically redistributed among surviving VSD boards.

Correct Answer: BC

QUESTION 2

A customer with a VSP G1000 is using HDT with SAS 15K drives and external storage. The customer wants the daytime response-sensitive workload to benefit from tiering. They also want to minimize the impact of relocations on the daytime operation itself.

In this scenario, which action will satisfy the requirements?

- A. Enable monitoring only during the daytime hours (9:00 AM to 5:00 PM) and only enable relocation at other times.
- B. Disable monitoring during daytime hours (9:00 AM to 5:00 PM)
- C. Enable active flash so that all relocations can be completed in short bursts.
- D. Use continuous mode with a 30-minute cycle time and define relocation during daytime hours (9:00 AM to 5:00 PM) with a low relocation speed.

Correct Answer: A

QUESTION 3

A customer complains about high response times. This occurs frequently with bursts of write I/O at 6,000 IOPS for 10 second periods during each minute. The write response is 60 ms during these 10 second periods. The average IOPS rate reported by Hitachi Tuning Manager over 1 minute is 600.

In this scenario, what is the average response time over 1 minute?

- A. 10 ms
- B. 30 ms
- C. 60 ms
- D. 90 ms



Correct Answer: A

QUESTION 4

Which two statements are true regarding HDP pools? (Choose two.)

- A. Using the largest possible pools is a recommended practice.
- B. Exposure to failure and recovery from failure must be considered when recommending the maximum size of a pool.
- C. HDP pools can be used for sizing HDT pools.
- D. Tier migration is based on performance and space capacity.

Correct Answer: AC

QUESTION 5

You are troubleshooting a potential marginal link in a SAN fabric that you believe is causing a performance problem.

To troubleshoot this problem, which two actions will allow you to view the detailed port statistics? (Choose two.)

- A. Use the vendor's GUI.
- B. Use the appropriate host command(s).
- C. Use the appropriate switch command(s).
- D. Use SVP Performance Monitor.

Correct Answer: AC

[Latest HCE-3700 Dumps](#)

[HCE-3700 Study Guide](#)

[HCE-3700 Exam Questions](#)