



HP2-Z32^{Q&As}

Implementing HP MSM Wireless Networks

Pass HP HP2-Z32 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hp2-z32.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which 802.11 frames can be sent at any supported rate (as opposed to the basic rate)?

- A. Broadcast frames
- B. Management frames
- C. Multicast frames
- D. Unicast frames

Correct Answer: D

QUESTION 2

802.11n	<input type="text"/>
802.11g	<input type="text"/>
802.11b	<input type="text"/>
802.11a	<input type="text"/>

Select the frequency band for each standard.

Hot Area:



802.11n

802.11g

802.11b

802.11a

Correct Answer:



802.11n

802.11g

802.11b

802.11a

QUESTION 3

A company has an MSM solution that includes an MSM 760 Controller and MSM APs. The VSC for the employees does not use the controller for access control, nor does it use wireless mobility. Employees' wireless clients should be assigned to VLAN 10. How should the Ethernet network administrators design VLAN 10?

- A. Extend VLAN 10 from its default router to the MSM Controller's LAN port.
- B. Extend VLAN 10 from its default router to the APs' switch ports
- C. Extend VLAN 10 from the MSM Controller's LAN port to the APs' switch ports.
- D. Extend VLAN 10 from its default router to the MSM Controller's Internet port.

Correct Answer: C

QUESTION 4

A network administrator maps a network profile with a VLAN ID 512 to the LAN port of an HP MSM765zI Mobility Controller. The network administrator configures an IP interface for this profile and intends to contact and manage the



controller

on this interface.

All other settings remain at default.

What is one step that the network administrator must complete before connecting to the controller on its new IP address?

- A. Set the untagged LAN port network interface IP address to none.
- B. Enable Spanning Tree Protocol (STP) on the interface.
- C. Select the new IP interface as an active interface in the Controller ?anagement>; Management tool window
- D. Set the IP interface as the authorized egress VLAN in the default VSC.

Correct Answer: D

QUESTION 5

What should match on HP MSM Controllers in order for the team to form properly?

Model (for example, MSM760 versus MSM765 zl)	<input type="text"/>
VLANs on switch ports on which team communications are established	<input type="text"/>
Number of AP licenses	<input type="text"/>
Port on which the team communications are established	<input type="text"/>

Hot Area:

Model (for example, MSM760 versus MSM765 zl)	<input type="text"/> Should match Does not need to match
VLANs on switch ports on which team communications are established	<input type="text"/> Should match Does not need to match
Number of AP licenses	<input type="text"/> Should match Does not need to match
Port on which the team communications are established	<input type="text"/> Should match Does not need to match

Correct Answer:



Model (for example, MSM760 versus MSM765 zl)

 Should match
 Does not need to match

VLANs on switch ports on which team communications are established

 Should match
 Does not need to match

Number of AP licenses

 Should match
 Does not need to match

Port on which the team communications are established

 Should match
 Does not need to match

[HP2-Z32 VCE Dumps](#)

[HP2-Z32 Study Guide](#)

[HP2-Z32 Braindumps](#)