



HP2-Z33^{Q&As}

HP Unified Wired-Wireless Networks and BYOD

Pass HP HP2-Z33 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hp2-z33.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

An organizations BOYD security policy states that if an employee wants to connect to the company\\'s wireless network with their personal devices, they must meet the following requirements:

1.
A digital certificate must be installed on the employee\\'s personal device and used to authenticate the device.

2.
The device must be authenticated using the local EAP authentication server.

Which EAP authentication method is available on the access controller to support this configuration?

- A. EAP-MSCHAPv2
- B. EAP-PEAP
- C. EAP-TLS
- D. EAP-TTLS

Correct Answer: C

QUESTION 2

A corporate user accesses a corporate network on SSID CORPORATE. The user endpoint is set up for 802.1X in PEAP-MSCHAPV2: HP BYOD is implemented.

Wireless is set up on an HP Unified Wired-Wireless Controller

Accounts have been synchronized with an Active Directory Domain controller.

- A. Setup of RADIUS on the Wireless controller and User Access Manager. Certificate server installation. BYOD Portal setup
- B. Setup of 802.1X Authentication on the wireless controller Installation of certificates in User Access Manager (UAM) Setup of RADIUS on the wireless controller and UAM
- C. Setup of 802 1X Authentication on the wireless controller Setup of RADIUS on the wireless controller and User Access Manager Fingerprinting with the DHCP agent
- D. Setup of 802 1X Authentication on the wireless controller Setup RADIUS on the wireless controller and User Access Manager Fingerprinting with the HTTP agent

Correct Answer: A

QUESTION 3

What is the maximum data rate that a 2x3 MIMO 802.11 n enabled device can transmit at?



- A. 54Mb/s
- B. 150 Mb/s
- C. 300 Mb/s
- D. 450 Mb/s

Correct Answer: C

QUESTION 4

Which customer requirements would cause a WLAN designer to recommend implementing an HP Unified Wired-Wireless enterprise controller? (Select two.)

- A. The customer currently has 500 access points and an HP MSM controller deployed, and they plan to deploy an additional 400 access points.
- B. The customer expects that the number of authenticated users will increase from 1500 to 2500.
- C. The customer wants to manage their wireless network using the HP IMC platform.
- D. The customer requires high availability and seamless failover of non-centralized traffic,
- E. The customer plans to deploy a new wireless network with 500 access points.

Correct Answer: CD

QUESTION 5

An administrator changes the setting for VLAN 200 on an HP 830 switch from tagged to untagged. How will this change affect the traffic sent over VLAN 200?

- A. Traffic sent over VLAN 200 will be forwarded to untagged VLAN 1.
- B. Tagged management traffic can no longer be sent on VLAN 200.
- C. Traffic sent over VLAN 200 will have the 802.1Q tag removed.
- D. Tagged traffic sent over VLAN 200 will be forwarded without changing the 802.1Q tag.

Correct Answer: C

[HP2-Z33 VCE Dumps](#)

[HP2-Z33 Study Guide](#)

[HP2-Z33 Braindumps](#)