



HP2-Z33^{Q&As}

HP Unified Wired-Wireless Networks and BYOD

Pass HP HP2-Z33 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hp2-z33.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which factors impact the calculation of the Effective Isotropic Radiated Power (EIRP)?

- A. antenna gain, cable loss, and transmit power
- B. propagation loss, receiver sensitivity, and transmit power
- C. antenna height, interference, and receiver signal strength
- D. antenna gain, propagation loss, and transmit power

Correct Answer: A

QUESTION 2

In an HP BYOD solution, what does DHCP fingerprinting provide?

- A. endpoint information
- B. web browser type
- C. SSID of the connection
- D. user account information

Correct Answer: A

QUESTION 3

Which action can a guest manager perform?

- A. Manage accounts of other guest managers.
- B. Create but not delete guest accounts.
- C. Set up corporate users as guests in the self-service page.
- D. Extend the lifetime of guest accounts.

Correct Answer: D

QUESTION 4

Which customer requirements would cause a WLAN designer to recommend implementing an HP Unified Wired-Wireless enterprise controller? (Select two.)

- A. The customer currently has 500 access points and an HP MSM controller deployed, and they plan to deploy an additional 400 access points.



- B. The customer expects that the number of authenticated users will increase from 1500 to 2500.
- C. The customer wants to manage their wireless network using the HP IMC platform.
- D. The customer requires high availability and seamless failover of non-centralized traffic,
- E. The customer plans to deploy a new wireless network with 500 access points.

Correct Answer: CD

QUESTION 5

A company plans to deploy an HP MSM wireless network. The company currently has a RADIUS server that is used to control employee access to the company's Intranet from wired clients. They want to use the same RADIUS server to control employee's access from wireless clients.

The company also wants to allow guests to connect to the wireless network. They want to allow the guests to reach the Internet, but they want to make sure that guests cannot reach the company's Intranet.

Based on these requirements, which traffic optimization scheme should be implemented?

- A. Deploy distributed forwarding for employees and distributed forwarding with centralized authentication for guests.
- B. Deploy distributed forwarding for employees and centralized access control for guests.
- C. Deploy centralized access control for employees and distributed forwarding with centralized authentication for guests.
- D. Deploy centralized access control for employees and distributed forwarding for guests.

Correct Answer: C

[HP2-Z33 VCE Dumps](#)

[HP2-Z33 Study Guide](#)

[HP2-Z33 Exam Questions](#)