



HPE0-J58^{Q&As}

Designing Multi-Site HPE Storage Solutions

Pass HP HPE0-J58 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hpe0-j58.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A customer wants to implement a disaster recovery plan for their current HPE 3PAR array data. They have obtained a remote site 10km away their primary site. They have performed bandwidth testing, and have confirmed their RTT is approximately 100ms. The customer needs to provide data replication to assure the best data availability they can achieve. Which synchronization method meets their needs?

- A. Asynchronous Streaming
- B. Asynchronous Periodic Remote Copy
- C. Synchronous Remote Copy
- D. Peer Persistence

Correct Answer: B

QUESTION 2

A customer has standardized on Windows Server. They need to ensure that application and storage will move between sites as one during automated or manual failover. Which HPE 3PAR integrated solution should you recommend to the customer as a preventative measure?

- A. Peer Persistence
- B. Serviceguard Metrocluster
- C. Cluster Extension (CLX)
- D. Site Recovery Manager

Correct Answer: C

Reference: https://tdhpe.techdata.eu/Documents/TDAS-Integrated%20Systems/Technical%20White%20Paper_HPE%20ConvergedSystem%20700.pdf?epslanguage=en

QUESTION 3

Refer to the exhibit, which reflects the Bill of Materials (BOM) configuration for one datacenter.



Qty	Product#		Product Description
2	QW937A		HPE SN3000B 16Gb 24-port/12-port Active Fibre Channel Switch
2	QW937A	05Y	2.4m Jumper (IEC320 C13/C14, M/F CEE 22)
24	QK724A		HPE B-series 16Gb SFP+Short Wave Transceiver
24	QK724A	0D1	Factory Integrated
1	H6Z07B		HPE 3PAR 8440 2N+SW Storage Field Base
2	H6Z00A		HPE 3PAR StoreServ 8000 4-port 16Gb Fibre Channel Adapter
8	K2P93B		HPE 3PAR 8000 1.2TB+SW 10K SFF HDD
8	M0T66B		HPE 3PAR 8000 3.84TB+SW SFF FE SSD
3	E7Y71A		HPE 3PAR StoreServ 8000 SFF(2.5in) Field Integrated SAS Drive Enclosure
24	K2P93B		HPE 3PAR 8000 1.2TB+SW 10K SFF HDD
24	M0T66B		HPE 3PAR 8000 3.84TB+SW SFF FE SSD
4	QK734A		HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable
2	Q9Y41AAE		HPE Smart Fabric Orchestrator E-LTU
24	QK735A		HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable
1	L7E71AAE		HPE 3PAR 8440 All-inc Multi-sys SW E-LTU
1	L7F20AAE		HPE 3PAR All-in S-sys SW Current E-Media
1	L7F22AAE		HPE 3PAR All-in M-sys SW Current E-Media

A customer needs a new storage solution of two HPE 3PAR 8440 arrays. The customer's environment consists of eight physical servers in each data center attached to the SAN and one StoreOnce 3540 system with two FC I/O cards. The

distance between data centers is less than 75 meters.

What should you add the BOM to meet the customer needs?

- A. one HPE 25m Mini SAS High Density Active Optical Cable for each HPE 3PAR 8440
- B. one HPR 3PAR StoreServ AC RPS Service Processor
- C. one HPE 3PAR StoreServ 8000 Direct Connect Cabling Option for Drive Enclosure for each HPE 3PAR 8440
- D. one HPE SN3000B SAN Switch 12-port Upgrade E-LTU per switch, appropriate number of SFPs and cables

Correct Answer: B

QUESTION 4

Refer to the exhibit.



C: DedupCrawler Q:

```

Scan      |#####|100%|00:04:33| 374MB/s
Analysis  |#####|100 %|00:00:02
|Drive|File   |Total |Written |After  |After   |Overall|Dedupe|Compress|
|Path|System  |Size  |non-zero|Dedupe|Compress|Ratio  |Ratio  |Ratio|
|Q:  |NTFS 16K |99.9GB |50.1GB |19.2GB |19.2GB |5.20  |2.60  |2.61|
  
```

A customer is considering a new HPE 3PAR for the purpose of implementing deduplication and compression. Based on the output returned from the NinjaCrawler tool, what do you know about the customer data?

- A. This data is a good candidate for HPE 3PAR deduplication
- B. This data has a video data workload profile
- C. This data is from an HP-UX system
- D. This data has a block size which is not optimal for HPE 3PAR

Correct Answer: A

QUESTION 5

A customer wants to enable an automated failover for their two existing HPE 3PAR solutions, which are located in two different sites. Each solution has an All-inclusive Single-System Software license. Which component is required to enable this function?

- A. All-inclusive Multi-System Software License
- B. Fibre channel Bridges to connect the disk shelves
- C. Additional HPE 3PAR system as quorum witness
- D. Dark fibre connection between the sites

Correct Answer: A

[Latest HPE0-J58 Dumps](#)

[HPE0-J58 VCE Dumps](#)

[HPE0-J58 Study Guide](#)