



# HPE0-J80<sup>Q&As</sup>

Delta - Architecting Multi-Site HPE Storage Solutions

## Pass HP HPE0-J80 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hpe0-j80.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Which tool should you use to quickly determine HPE 3PAR StoreServ health and performance?

- A. Command View 3PAR
- B. SSMC
- C. 3PAR CLI
- D. CMC

Correct Answer: B

---

### QUESTION 2

You are designing an HPE 3PAR StoreServ environment using HPE Smart SAN Which solution components are supported? (Select two.)

- A. Emulex HBAs
- B. HPE 5900 CP switches
- C. Qlogic Fibre Channel HBAs
- D. HPE H-series SAN switches
- E. Physical 3PAR Service Processor

Correct Answer: BC

---

### QUESTION 3

A storage architect is reviewing customer as-built documentation. The solution architect discovers that there are Windows Server 2003 machines that will be virtualized in an ESXi 5.5 environment connected to an HPE 3 PAR StoreServ.

What should be considered in the MPIO implementation design?

- A. The HPE 3PAR array will handle load balancing on the hardware level
- B. HPE 3PAR Multipath I/O should be used for Microsoft Windows 2003
- C. MPIO will be handled natively by the ESXi host software
- D. MPIO must be set to use MRU

Correct Answer: B

---

**QUESTION 4**

Which requirements must be considered when designing and sizing an HPE 3PAR StoreServ environment for periodic asynchronous replication?

- A. Size only the source array to account for the IOPS resulting from snapshot created by Remote Copy.
- B. Size both arrays to account for the IOPS resulting from snapshots created by Remote Copy.
- C. Use a CPG with SAS drives for Remote Copy snapshots.
- D. Size only the target array to account for IOPS resulting from snapshots created by Remote Copy.
- E. Use a CPG with nearline drives for Remote Copy snapshots.

Correct Answer: AE

---

**QUESTION 5**

You are designing an iSCSI solution for a customer with one data center, who is investing in a second data center that will be ready in the near future. The networking infrastructure of the current data center is generally sufficient for use with an iSCSI storage solution, but it is from a different vendor. The new data center will be equipped with current HPE Networking switches.

- A. For maximum performance, Jumbo Frames should be configured on the storage nodes only
- B. Jumbo Frames are only required for low latency applications
- C. Jumbo Frame sizes are not standardized across all switch vendors
- D. Only switch ports must be configured to forward Jumbo Frames

Correct Answer: C

[Latest HPE0-J80 Dumps](#)

[HPE0-J80 PDF Dumps](#)

[HPE0-J80 Exam Questions](#)