

# HPE0-J80<sup>Q&As</sup>

Delta - Architecting Multi-Site HPE Storage Solutions

# Pass HP HPE0-J80 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/hpe0-j80.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

😳 365 Days Free Update

800,000+ Satisfied Customers





#### **QUESTION 1**

The demonstration of iSCSI Persistent Ports during an HPE 3PAR StoreServ proof of concept fails. What is a possible cause of failure?

- A. The connected switch gets a loss\_sync of the HPE 3PAR StoreServ port and disconnects the port immediately.
- B. The connected switch does not accept an unsolicited ARP and does not update the IP address mappings.
- C. Zoning is not implemented correctly, and the host could not connect to the partner port.
- D. Port Persistence is not configured correctly, so the partner port could not be activated in a timely manner.

Correct Answer: D

### **QUESTION 2**

At which level is an HPE 3PAR StoreServ deduplication performed?

- A. CPG
- B. VV
- C. RAID
- D. RCG

Correct Answer: C

#### **QUESTION 3**

Which requirements must be considered when designing and sizing an HPE 3PAR StoreServ environment for periodic asynchronous replication?

- A. Size only the source array to account for the IOPS resulting from snapshot created by Remote Copy.
- B. Size both arrays to account for the IOPS resulting from snapshots created by Remote Copy.
- C. Use a CPG with SAS drives for Remote Copy snapshots.
- D. Size only the target array to account for IOPS resulting from snapshots created by Remote Copy.
- E. Use a CPG with nearline drives for Remote Copy snapshots.

Correct Answer: AE

### **QUESTION 4**

Which information should be collected and analyzed when discovering customer expectations for replication



performance? (Select two.)

- A. rate of data change
- B. bandwidth
- C. type of data
- D. latency
- E. frequency of copies

Correct Answer: AD

## **QUESTION 5**

A customer has almost reached the maximum number of domain IDs in a B-series, Fibre Channel SAN fabric. The company has also recently acquired another company and needs to integrate their C-series Fibre Channel SAN to be able to share the SAN infrastructure.

Which feature should you enable on the C-series, Fibre Channel edge switches to meet these requirements?

- A. NPV mode
- B. FSPF routing
- C. hard zoning
- D. soft zoning
- Correct Answer: C

Latest HPE0-J80 Dumps

HPE0-J80 PDF Dumps

HPE0-J80 Exam Questions