



HPE6-A15^{Q&As}

Aruba Certified Clearpass Professional 6.5

Pass HP HPE6-A15 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hpe6-a15.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which settings need to be validated for a successful EAP-TLS authentication? (Select two.)

- A. Username and Password
- B. Pre-shared key
- C. WPA2-PSK
- D. server Certificate
- E. Client Certificate

Correct Answer: DE

When you use EAP with a strong EAP type, such as TLS with smart cards or TLS with certificates, both the client and the server use certificates to verify their identities to each other. Certificates must meet specific requirements both on the server and on the client for successful authentication.

References: <https://support.microsoft.com/en-us/help/814394/certificate-requirements-when-you-use-eap-tls-or-peap-with-eap-tls>

QUESTION 2

Refer to the exhibit.



Home >> Configuration >> Web Logins

RADIUS Web Login

Use this form to make changes to the RADIUS Web Login **Guest Network**.

RADIUS Web Login Editor	
* Name:	<input type="text" value="Guest Network"/> Enter a name for this web login page.
Page Name:	<input type="text" value="Aruba_login"/> Enter a page name for this web login. The web login be accessible from <code>"/guest/page_name.php"</code> .
Description:	<div></div> Comments or descriptive text about the web login.
* Vendor Settings:	<input type="text" value="Aruba Networks"/> Select a predefined group of settings suitable for standard network configurations.
Address:	<input type="text" value="securelogin.arubanetworks.com"/> Enter the IP address or hostname of the vendor's product here.
Secure Login:	<input type="text" value="Use vendor default"/> Select a security option to apply to the web login process.
Dynamic Address:	<input type="checkbox"/> The controller will send the IP to submit credentials In multi-controller deployments, it is often required to post credentials to different addresses. The address above will be used whenever the parameter is not available or fails.

When configuring a Web Login Page in ClearPass Guest, the information shown is displayed.

What is the Address field value `'securelogin.arubanetworks.com'` used for?

- A. for ClearPass to send a TACACS+ request to the NAD
- B. for appending to the Web Login URL, before the page name
- C. for the client to POST the user credentials to the NAD
- D. for ClearPass to send a RADIUS request to the NAD
- E. for appending to the Web Login URL, after the page name.

Correct Answer: C

QUESTION 3



An employee provisions a personal smart phone using the Onboard process. In addition, the employee has a corporate laptop provided by IT that connects to the secure network. How many licenses does the employee consume?

- A. 1 Policy Manager license, 2 Guest Licenses
- B. 2 Policy Manager licenses, 1 Onboard License
- C. 1 Policy Manager license, 1 Onboard License
- D. 1 Policy Manager license, 1 Guest License
- E. 2 Policy Manager licenses, 2 Onboard Licenses

Correct Answer: B

QUESTION 4

Refer to the exhibit.

Configuration » Identity » Role Mappings » Edit - [Guest Roles]

Role Mappings - [Guest Roles]

Summary Policy **Mapping Rules**

Rules Evaluation Algorithm: ☒ Select first match ☐ Select all matches

Role Mapping Rules:

	Conditions	Role Name
1.	(GuestUser:Role ID EQUALS 1)	[Contractor]
2.	(GuestUser:Role ID EQUALS 2)	[Guest]
3.	(GuestUser:Role ID EQUALS 3)	[Employee]
4.	(GuestUser:Role ID EQUALS 4)	Test guest role creation

Add Rule Move Up Move Down

Based on the Guest Role Mapping Policy shown, what is the purpose of the Role Mapping Policy?

- A. to display a role name on the Self-registration receipt page
- B. to send a firewall role back to the controller based on the Guest User's Role ID
- C. to assign Controller roles to guests
- D. to assign three roles of [Contractor], [Guest] and [Employee] to every guest user
- E. to create additional account roles for guest administrators to assign to guest accounts

Correct Answer: C

QUESTION 5

An SNMP probe is sent from ClearPass to a network access device, but ClearPass is unable to obtain profiling information. What are likely causes? (Select three.)



- A. Only SNMP read has been configured but SNMP write is needed for profiling information.
- B. An external firewall is blocking SNMP traffic.
- C. SNMP is not enabled on the NAD.
- D. SNMP community string in the ClearPass and NAD configuration is mismatched.
- E. SNMP probing is not supported between ClearPass and NADs.

Correct Answer: BCD

Verify firewall port 162 (default) is open between AMP and the controller.

SNMP must be enabled on the NAD.

The community string that ClearPass is using to access the NAD might be wrong.

References: <https://community.arubanetworks.com/t5/Monitoring-Management-Location/SNMP-Get-Failed-quot-error-message/ta-p/169774>

[HPE6-A15 PDF Dumps](#)

[HPE6-A15 VCE Dumps](#)

[HPE6-A15 Exam Questions](#)