



HPE6-A66^{Q&As}

Aruba Certified Design Associate Exam

Pass HP HPE6-A66 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hpe6-a66.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

NewRocket requires a wireless capacity design 30 Aruba 510 APs will be connected to each wiring closet using SmartRate connections. Wireless coverage needs to be provided even if a POE+ switch loses power

Because of security concerns, wired video cameras were recently installed throughout the facility. There are 12 of these per floor. 6 per wiring closet. The cameras are 802.11n WiFi capable and have power injectors from which to draw power.

Based on the POE+ needs of the mentioned devices, which solution would meet the POE+ requirements while still providing a redundant and cost-effective Wi-Fi solution for the devices that require POE+ for Building 1, Floor 2?

- A. One 3810M 40G 8 HPE Smart Rate switch
- B. Two 2930F 24-port POE+ switches
- C. Two 2930M 24-port POE+ switches
- D. One 2930M 48-port POE+ switch

Correct Answer: D

QUESTION 2

A company is redesigning their wireless network and will be upgrading all devices to support the latest wireless standards. The company is not near any radar installations. In order to keep wireless NIC power levels as low as possible to reduce interference issues and to take advantage of radar frequency ranges, what IEEE standard should APs support?

- A. 802.11r
- B. 802.11 ax
- C. S02.11V
- D. S02.11h

Correct Answer: B

QUESTION 3

A network architect is redesigning a wireless network. The architect begins by analyzing the number of spatial streams supported by APs of various vendors as well as the wireless devices currently in the network, if the company wants to ensure that new wireless design, including user wireless devices, support Multi-User MIMO (MU-MIMO). Which standard or standards must the wireless products support?

- A. Only 802.11ax and 8011.ac
- B. Only 802.11ax



C. Only 802.11ax,802.11ac, and 802.11n

D. Only 802.11ax,802.11ac, 802.11n, and 802.11a

Correct Answer: C

QUESTION 4

A network architect is redesigning the access layer in a data center for a customer. The access layer requires fixed-port switches that support VSF and data center features like L2 VXLAN and REST-API. Which switching solution should the network architect recommend?

A. 8400

B. 3810M

C. 2930F

D. 6300

Correct Answer: C

QUESTION 5

A network architect needs to plan a new wireless network:

A. Central only

B. Airwave and Central only

C. Airwave, Central, Windows, Mac OSX, and Linux

D. Airwave, Central, and Windows only

Correct Answer: B

[HPE6-A66 PDF Dumps](#)

[HPE6-A66 Practice Test](#)

[HPE6-A66 Study Guide](#)