



HPE6-A66^{Q&As}

Aruba Certified Design Associate Exam

Pass HP HPE6-A66 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hpe6-a66.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A company has chosen an Aruba mobility controller solution for the redesign of their wireless network. The design will have two 7205 controllers in a cluster for campus employees and a single VMC-50 virtual controller for remote access via a

DMZ. A Mobility Master (MM) is used for centralized license and controller management. All controllers will minimally run ArubaOS 8.4 or later. Currently, the company has 1,000 employees. There are 30 branch offices that will use RAPs to

connect to the DMZ controller. A peak of 100 users concurrently using the VIA client will also connect to the DMZ controller.

How many Aruba LIC-VIA licenses does the company need to purchase for this solution?

- A. 100
- B. 1
- C. 1,030
- D. 130

Correct Answer: C

QUESTION 2

A customer has over 100 access layer switches. The customer requires user authentication done via the Aruba Dynamic Segmentation feature. What components are required to implement this solution? (Select two.)

- A. enterprise authentication server
- B. Aruba APs
- C. Aruba mobility controller
- D. AirWave server
- E. Active Directory server

Correct Answer: CD

QUESTION 3

Which component uniquely defines the BSSID when implementing an employee SSID?

- A. Case-sensitive SSID name
- B. Radio MAC address
- C. Wireless device MAC address



D. Case-insensitive SSID name

Correct Answer: C

QUESTION 4

A customer requires a campus core virtualization solution that supports a dual control and management planes, as well as active-active forwarding paths. Which solution would meet the customer's requirements?

- A. Mesh stacking
- B. VSX
- C. Backplane stacking
- D. VSF

Correct Answer: C

QUESTION 5

A network architect is designing a new Wi-Fi solution for a customer. The customer currently occupies a one-story building on a small campus. In one part of the building there is an auditorium, where the ceiling height and attenuation is different from the rest of the building. What should the network architect create in VisualRF to identify this difference when planning the APs?

- A. Define the appropriate properties in the Network View
- B. Create a Region in the Floorplan View
- C. Split the Building View into two Floorplan Views
- D. Define the appropriate properties in the Building View

Correct Answer: D

[HPE6-A66 PDF Dumps](#)

[HPE6-A66 Practice Test](#)

[HPE6-A66 Exam Questions](#)