



ISS-003^{Q&As}

Intel Server Specialist Certification Exam

Pass CompTIA ISS-003 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/iss-003.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CompTIA
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A customer has spent a long time on the phone with their reseller and the reseller is now talking to you about how to remotely access the RAID controller on an Intel® Server that has been correctly supplied and configured, with RAID Web Console 2. You have been told by your reseller that the server board in question has 4 on-board NICS. What will you recommend? (Select ALL that apply).

- A. Only clients on the same subnet as the highest No. NIC interface will be able to remotely manage the RAID Server via RWC2
- B. Suggest that the customer disable all network ports and only manage the RAID from the server directly
- C. If there is more than one Ethernet port on the server, access to the RAID information is only available on the highest No. NIC interface.
- D. Suggest that the customer disable all network ports except the highest and manage the RAID from the server directly

Correct Answer: AC

QUESTION 2

Your customer has asked you to enable BMC management and remote access. They are now asking you to walk them through the different features which are available via the Embedded Web Server. They would like to see what the current power draw of the server is. Please choose all the correct answers from the list below:

- A. Configuration Tab, Node Manager and Power Monitor
- B. System Information Tab and power monitor
- C. Server Health Tab and Power statistics
- D. System Information Tab, FRU Information and Power Monitor

Correct Answer: C

QUESTION 3

During a FRUSDR update on an Intel Server System SR2208WTTYS a customer has flashed the wrong FRU file and inserted an unnecessary field. Which one of the following actions can help to reset FRU fields to default values and allow removal of the extra field?

- A. frusdr.efi /cfg master.cfg
- B. Flash BMC image in BMC Force Update mode
- C. syscfg /rbmc
- D. frusdr.efi/fruS2600WTT.fru

Correct Answer: D



QUESTION 4

Your customer has asked you the Intel Server Specialist for confirmation on the process following changes to their server (additional memory, a different raid card and a 40Gb Ethernet card)? What must they do to ensure accurate monitoring of all the sensors in their S2600WT based server?

- A. The FRU/SDR must be updated with the latest master.cfg to enable the new hardware to be detected.
- B. They don't need to do anything - the current firmware will auto-configure.
- C. The ME must be updated prior to use of the master.cfg and then the FRUSDR update may be carried out.
- D. Only the FRU needs to be updated as the SDR now auto-configures
- E. Only the SDR needs to be updated as the FRU auto-configures.

Correct Answer: B

QUESTION 5

Which of the following memory modules can be used in the Intel Server Board S1200V3RP? Please choose your answer from the list below.

- A. Non ECC LRDIMM
- B. Non-ECC UDIMM
- C. ECC RDIMM
- D. ECC LRDIMM
- E. Non-ECC RDIMM
- F. ECC UDIMM

Correct Answer: F

[ISS-003 VCE Dumps](#)

[ISS-003 Study Guide](#)

[ISS-003 Exam Questions](#)