JAVASCRIPT-DEVELOPER-I Q&As

Salesforce Certified JavaScript Developer I

Pass Salesforce JAVASCRIPT-DEVELOPER-I Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/javascript-developer-i.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Salesforce Official Exam Center

- **Instant Download** After Purchase
- **100% Money Back** Guarantee
- **365 Days** Free Update
- **800,000+** Satisfied Customers

QUESTION 1

Given the code below:

```
Function myFunction(){
A =5;
Var b =1;
}
myFunction();
console.log(a);
console.log(b);
```

What is the expected output?

A. Both lines 08 and 09 are executed, and the variables are outputted.

B. Line 08 outputs the variable, but line 09 throws an error.

C. Line 08 thrones an error, therefore line 09 is never executed.

D. Both lines 08 and 09 are executed, but values outputted are undefined.

Correct Answer: B

QUESTION 2

Refer to the code below:

```
Function changeValue(obj) {
Obj.value =obj.value/2;
}
Const objA = (value: 10);
Const objB = objA;
changeValue(objB);
Const result = objA.value;
```

What is the value of result after the code executes?

A. 10

B. Nan

C. 5

D. Undefined

Correct Answer: C

QUESTION 3

Refer to the code below:

let timeFunction =() => {

console.log(`Timer called.");

};

let timerId = setTimeout (timedFunction, 1000);

Which statement allows a developer to cancel the scheduled timed function?

A. removeTimeout(timedFunction);

B. removeTimeout(timerId);

C. clearTimeout(timerId);

D. clearTimeout(timedFunction);

Correct Answer: C

QUESTION 4

Refer to the code snippet below:

Let array = [1, 2, 3, 4, 4, 5, 4, 4];

For (let i =0; i {

console.log(\\'Grr!\\');

}

}

Option B:

function Monster(){};

Monster.prototype.growl = ()=>{

console.log(\\'Grr!\\');

}

After deciding on an option, the developercreates 1000 monster objects.

How many growl methods are created with Option A and Option B?

A. 1000 for Option A, 1 for Option B

B. 1 methods for both

C. 1000 for both

D. 1 for Option A, 1000 for Option B

Correct Answer: B

JAVASCRIPT-DEVELOPER-I PDF Dumps | JAVASCRIPT-DEVELOPER-I Practice Test | JAVASCRIPT-DEVELOPER-I Exam Questions