



JK0-023^{Q&As}

CompTIA Network+ certification

Pass CompTIA JK0-023 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jk0-023.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CompTIA
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A technician is configuring a new DSL router. The technician can communicate with the LAN but not the WAN. Which of the following is the MOST likely cause?

- A. Duplicate IP addresses
- B. Bad GBIC
- C. Wrong gateway
- D. Switching loop

Correct Answer: C

QUESTION 2

A client has just leased a new office space in a busy commercial building and would like to install a wireless network. Several other tenants are on the same floor. Multiple wireless networks are present in the building. Which of the following can be changed on the client's wireless network to help ensure that interference from other wireless networks is at a minimum?

- A. WPA encryption key selection
- B. Channel selection
- C. Antenna types
- D. Disable SSID

Correct Answer: B

QUESTION 3

A network administrator detects an existing 802.11g signal on channel 5. Which of the following channels would be the LEAST likely to interfere with the existing signal?

- A. 1
- B. 6
- C. 9
- D. 11

Correct Answer: D

QUESTION 4



Kimf a technicianf needs to locate a cable in an unorganiiied wiring closet. Which of the following tools will help her locate the cable?

- A. Protocol analyier
- B. Cable tester
- C. Toner probe
- D. Punch down tool

Correct Answer: C

QUESTION 5

Users have contacted the helpdesk statng that they have been having difcultes staying connected to the wireless network. They report that their laptops connect to one access pointf drop the connecton and then connect to a diferent access point in a never-ending cycle. Which of the following would BEST remediate this?

- A. Reconfigure the access points from 802.11b to 802.11g.
- B. Establish procedures which limit user connectons during peak hours.
- C. Configure the access points so that they all use diferent SSIDs.
- D. Move one or more access pointsf minimiing signal overlap.

Correct Answer: D

[Latest JK0-023 Dumps](#)

[JK0-023 Practice Test](#)

[JK0-023 Study Guide](#)