



JN0-1331^{Q&As}

Security Design - Specialist (JNCDS-SEC)

Pass Juniper JN0-1331 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-1331.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You are concerned about malicious attachments being transferred to your e-mail server at work through encrypted channels. You want to block these malicious files using your SRX Series device.

Which two features should you use in this scenario? (Choose two.)

- A. Sky ATP SMTP scanning
- B. Sky ATP HTTP scanning
- C. SSL forward proxy
- D. SSL reverse proxy

Correct Answer: AC

Reference: https://www.juniper.net/documentation/en_US/release-independent/sky-atp/help/informationproducts/pathway-pages/email-scanning-sky-atp.html

QUESTION 2

You are deploying a data center Clos architecture and require secure data transfers within the switching fabric.

In this scenario, what will accomplish this task?

- A. MACsec encryption
- B. LAG Layer 2 hashing
- C. IRB VLAN routing between hosts
- D. stacked VLAN tagging on the core switches

Correct Answer: C

Reference: https://www.juniper.net/documentation/en_US/junos/topics/example/private-vlans-irbinterfaces-mx-series-l2ng-configuring.html

QUESTION 3

You have multiple SRX chassis clusters on a single broadcast domain. Why must you assign different cluster IDs in this scenario?

- A. to avoid MAC address conflicts
- B. to avoid control link conflicts
- C. to avoid node numbering conflicts
- D. to avoid redundancy group conflicts

Correct Answer: A



Reference: https://www.juniper.net/documentation/en_US/release-independent/nce/topics/example/chassis-cluster-srx-full-mesh-configuring.html#:~:text=If%20you%20have%20multiple%20SRX,other%20device%20is%20node%201.

QUESTION 4

You work for an ISP that wants to implement remote-triggered black hole (RTBH) filters. What are three considerations in this scenario? (Choose three.)

- A. Source RTBH can block legitimate traffic on the network
- B. BGP FlowSpec improves the RTBH model by implementing dynamic firewall filters
- C. Source RTBH requires uRPF to be implemented on the service provider's network core
- D. Destination RTBH requires uRPF to be implemented on the service provider's network edge
- E. Destination RTBH essentially completes the attack on the victim's IP

Correct Answer: ABC

QUESTION 5

You are asked to install a mechanism to protect an ISP network from denial-of-service attacks from a small number of sources.

Which mechanism will satisfy this requirement?

- A. RTBH
- B. UTM
- C. Sky ATP
- D. GeoIP

Correct Answer: A

Reference: https://www.juniper.net/documentation/en_US/day-one-books/DO_BGP_FlowSpec.pdf