



JN0-1332^{Q&As}

Security Design Specialist (JNCDS-SEC)

Pass Juniper JN0-1332 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-1332.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

You must design a small branch office firewall solution that provides application usage statistics.

In this scenario, which feature would accomplish this task?

- A. AppFW
- B. AppTrack
- C. UTM
- D. AppQoS

Correct Answer: B

Reference: https://www.juniper.net/documentation/en_US/junos/topics/topic-map/security-applicationtracking.html

QUESTION 2

You are asked to install a mechanism to protect an ISP network from denial-of-service attacks from a small number of sources.

Which mechanism will satisfy this requirement?

- A. RTBH
- B. UTM
- C. Sky ATP
- D. GeoIP

Correct Answer: A

Reference: https://www.juniper.net/documentation/en_US/day-one-books/DO_BGP_Flowspec.pdf

QUESTION 3

You are creating a data center security design. Virtual security functions must be performed on east-west traffic. Security functions must be commissioned and decommissioned frequently, and the least resource-intensive architecture must be used.

In this scenario, what will accomplish this task?

- A. all-in-one NFV security devices with device templates
- B. service chaining with container-based security functions
- C. a security appliance segmented into logical systems



D. filter-based forwarding to direct traffic to the required security devices

Correct Answer: A

QUESTION 4

You are asked to provide a design proposal for a campus network. As part of the design, the customer requires that all end user devices must be authenticated before being granted access to their Layer 2 network.

Which feature meets this requirement?

- A. IPsec
- B. 802.1X
- C. NAT
- D. ALGs

Correct Answer: B

Reference: https://www.juniper.net/documentation/en_US/junos/topics/topic-map/802-1x-authenticationswitching-devices.html

QUESTION 5

You have multiple SRX chassis clusters on a single broadcast domain. Why must you assign different cluster IDs in this scenario?

- A. to avoid MAC address conflicts
- B. to avoid control link conflicts
- C. to avoid node numbering conflicts
- D. to avoid redundancy group conflicts

Correct Answer: A

Reference: https://www.juniper.net/documentation/en_US/release-independent/nce/topics/example/chassis-cluster-srx-full-mesh-configuring.html#:~:text=If%20you%20have%20multiple%20SRX,other%20device%20is%20node%201.

[JN0-1332 Practice Test](#)

[JN0-1332 Exam Questions](#)

[JN0-1332 Braindumps](#)