



# JN0-1361<sup>Q&As</sup>

Service Provider Design Specialist (JNCDS-SP)

**Pass Juniper JN0-1361 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-1361.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

You are asked to improve the convergence time in your large enterprise WAN. Each branch office network is multihomed to two central aggregation points using BGP.

Which action would satisfy the requirement?

- A. Provision more WAN bandwidth.
- B. Increase interface hold timers.
- C. Decrease interface hold timers.
- D. Use Bidirectional Forwarding Detection.

Correct Answer: D

---

### QUESTION 2

What are three components of a class-of-service scheduler? (Choose three.)

- A. transmit rate
- B. forwarding class
- C. queue priority
- D. delay buffer size
- E. policing rate

Correct Answer: ACD

Junos OS schedulers allow you to define the priority, bandwidth, delay buffer size, rate control status, and RED drop profiles to be applied to a particular queue for packet transmission

---

### QUESTION 3

MPLS services are being delivered from provider edge (PE) routers. Each PE is connected to multiple customer edge (CE) routers.

What should you use on the PE to isolate customer routes?

- A. VPN routing and forwarding tables
- B. access control lists
- C. external BGP



D. port access control lists

Correct Answer: A

---

#### QUESTION 4

What are two considerations for all WAN designs that use best industry practices? (Choose two )

- A. to provide a dynamic routing protocol internally in the LAN
- B. to provide scalability
- C. to provide ease of deployment
- D. to provide VXLAN and EVPN solutions

Correct Answer: BC

---

#### QUESTION 5

You are designing a multi-site data center environment with data center interconnects between sites. Which two statements are true in this scenario? (Choose two. )

- A. VPLS can be used to interconnect the multiple sites.
- B. EVPN with VXLAN can be used to interconnect the multiple sites.
- C. The data centers must be connected with a full mesh design.
- D. All data centers must be in the same Layer 2 broadcast domain and subnet.

Correct Answer: AB

[JN0-1361 PDF Dumps](#)

[JN0-1361 VCE Dumps](#)

[JN0-1361 Practice Test](#)