



# JN0-250<sup>Q&As</sup>

Mist AI, Associate (JNCIA-MistAI)

## Pass Juniper JN0-250 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-250.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

You are configuring your Mist network and you want to separate certain users into their own networks and VLANs. You are concerned about the network's utilization and want to make sure that only a single SSID is sending beacons.

In this scenario, which feature would accomplish this behavior?

- A. geofence
- B. multiple PSK
- C. virtual SSID
- D. SSID scheduling

Correct Answer: D

---

### QUESTION 2

When would be the earliest opportunity to configure an access point (AP)?

- A. after you are on the same network as the AP
- B. after the AP is installed
- C. after the AP is online
- D. after the AP is claimed to inventory

Correct Answer: B

---

### QUESTION 3

You have just brought online a new site of AP43s. While verifying that everything looks good, you notice that all of the access points (APs) are reporting "insufficient power." The APs are connected to an 802.3at-capable switch.

In this scenario, what would be the cause of the error?

- A. The cable run to each AP is too long.
- B. The Ethernet cable is plugged into the wrong port on the AP.
- C. The APs' firmware must be upgraded.
- D. LLDP-MED is not configured on the switch.

Correct Answer: C

---

### QUESTION 4



---

Under ideal conditions, which frequency band will have the farthest usable range?

- A. 900 MHz
- B. 2.4 GHz
- C. 5 GHz
- D. 6 GHz

Correct Answer: B

---

#### QUESTION 5

By default, which statement is correct regarding the upstream interfaces configuration on a Mixtape?

- A. The Interface is configured to send untagged traffic.
- B. The interface is configured as a trunk port and accepts only tagged traffic.
- C. The interface is configured to use VLAN 10.
- D. The Interface is configured to use VLAN 11.

Correct Answer: B

[Latest JN0-250 Dumps](#)

[JN0-250 Practice Test](#)

[JN0-250 Study Guide](#)