



# JN0-333<sup>Q&As</sup>

Security, Specialist (JNCIS-SEC)

## Pass Juniper JN0-333 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-333.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





### QUESTION 1

Which SRX5400 component is responsible for performing first pass security policy inspection?

- A. Routing Engine
- B. Switch Control Board
- C. Services Processing Unit
- D. Modular Port Concentrator

Correct Answer: C

---

### QUESTION 2

Your network includes IPsec tunnels. One IPsec tunnel transits an SRX Series device with NAT configured. You must ensure that the IPsec tunnels function properly.

Which statement is correct in this scenario?

- A. Persistent NAT should be enabled.
- B. NAT-T should be enabled.
- C. Destination NAT should be configured.
- D. A source address pool should be configured.

Correct Answer: B

---

### QUESTION 3

You want to ensure that any certificates used in your IPsec implementation do not expire while in use by your SRX Series devices.

In this scenario, what must be enabled on your devices?

- A. RSA
- B. TLS
- C. SCEP
- D. CRL

Correct Answer: C

---

### QUESTION 4



---

Which two modes are supported during the Phase 1 IKE negotiations used to establish an IPsec tunnel? (Choose two.)

- A. transport mode
- B. aggressive mode
- C. main mode
- D. tunnel mode

Correct Answer: BC

---

#### QUESTION 5

You are asked to support source NAT for an application that requires that its original source port not be changed.

Which configuration would satisfy the requirement?

- A. Configure a source NAT rule that references an IP address pool with interface proxy ARP enabled.
- B. Configure the egress interface to source NAT fixed-port status.
- C. Configure a source NAT rule that references an IP address pool with the port no-translation parameter enabled.
- D. Configure a source NAT rule that sets the egress interface to the overload status.

Correct Answer: C

[Latest JN0-333 Dumps](#)

[JN0-333 Exam Questions](#)

[JN0-333 Braindumps](#)