



JN0-334^{Q&As}

Security-Specialist (JNCIS-SEC)

Pass Juniper JN0-334 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-334.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

When working with network events on a Juniper Secure Analytics device, flow records come from which source?

- A. tap port
- B. SPAN
- C. switch
- D. mirror

Correct Answer: B

Reference: https://www.juniper.net/documentation/en_US/jsa7.3.1/jsa-arch-deployment-guide/topics/concept/jsa-ad-jsa-events-and-flows.html

QUESTION 2

What is the default timeout period for a TCP session in the session table of a Junos security device?

- A. 1 minute
- B. 60 minutes
- C. 15 minutes
- D. 30 minutes

Correct Answer: D

QUESTION 3

In an Active/Active chassis cluster deployment, which chassis cluster component is responsible for RG0 traffic?

- A. the backup routing engine of the primary node
- B. the master routing engine of the secondary node
- C. the primary node
- D. the secondary node

Correct Answer: C

**QUESTION 4**

Click the Exhibit button.

```
Exhibit
user@srx> show services user-identification identity-management status
Primary server :
  Address      : 172.25.11.130
  Port        : 443
  Connection method : HTTPS
  Connection status : Online
  Last received status message : invalid_client(400)
  Access token  : NULL
Secondary server :
  Address      : Not configured
```

You have configured your SRX Series device to receive authentication information from a JIMS server. However, the SRX is not receiving any authentication information.

Referring to the exhibit, how would you solve the problem?

- A. Use the JIMS Administrator user interface to add the SRX device as a client.
- B. Generate an access token on the SRX device that matches the access token on the JIMS server.
- C. Update the IP address of the JIMS server
- D. Change the SRX configuration to connect to the JIMS server using HTTP.

Correct Answer: B

QUESTION 5



You are asked to improve resiliency for individual redundancy groups in an SRX4600 chassis cluster. Which two features would accomplish this task? (Choose two.)

- A. IP address monitoring
- B. control link recovery
- C. interface monitoring
- D. dual fabric links

Correct Answer: BD

[Latest JN0-334 Dumps](#)

[JN0-334 Study Guide](#)

[JN0-334 Braindumps](#)