



JN0-347^{Q&As}

Enterprise Routing and Switching, Specialist (JNCIS-ENT)

Pass Juniper JN0-347 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-347.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Click the Exhibit button.

```
[edit]
user@host# show protocols isis
level 2 disable;
interface ge-0/0/1.0;
interface ge-0/0/2.0;
interface ge-0/0/3.0;
interface lo0.0;

[edit]
user@host#
```

Referring to the exhibit, which two statement are true? (Choose two.)

- A. The device will not form adjacencies with devices in a different area;
- B. The Level 2 database will be empty.
- C. The IS-IS protocol is disabled on the device.
- D. The device will not have a Level 2 database.

Correct Answer: AB

QUESTION 2

Click the Exhibit button.

```
user@host> show route hidden

inet.0: 40472 destinations, 83201 routes (43201 active, 0 holddown, 1 hidden)
+ = Active Route, - = Last Active, * = Both

0.0.0.0/0          [Aggregate] 06:55:56
                   Discard
```

Referring to the exhibit, why is the 0.0.0.0/0 route hidden?

- A. The next hop is set to discard.
- B. You already have an active BGP default route.
- C. You cannot make a 0.0.0.0/0 generated route.
- D. There are no contributing routes.



Correct Answer: D

QUESTION 3

Click the Exhibit button.

```
{master:0}[edit]
user@host# show vlans
data {
  vlan-id 34;
  forwarding-options {
    dhcp-security {
      arp-inspection;
      group data {
        overrides {
          trusted;
        }
        interface xe-0/2/3.0;
      }
    }
  }
}
```

Referring to the exhibit, a packet tagged with vlan-id 34 arrives on interface xe-0/2/3.0 with a source MAC that does not match an entry in the DHCP snooping database.

In this scenario, which statement is correct?

- A. The source MAC is added to the DHCP snooping database.
- B. An error message is logged and the packet is forwarded.
- C. The destination MAC added to the DHCP snooping database.
- D. The packet is forwarded and no error message is logged.

Correct Answer: A

QUESTION 4

Which mechanism is used to share routes between routing tables?

- A. filter-based forwarding
- B. forwarding instances
- C. RIB groups
- D. routing instances



Correct Answer: C

A RIB group is a way to have a routing protocol, in most cases, place information in multiple route tables.

QUESTION 5

You received an alert from your monitoring system that the master Routing Engine (RE) on an EX4300 switch in a virtual chassis has hardware issues and might need to be replaced. Because the switch already had graceful Routing Engine switchover (GRES) enabled and configured, you must perform a manual switchover to the backup CK to avoid disruption. Which command would be used to perform the manual CK switchover?

- A. Log in to the backup CK and issue the request chassis-control operation command.
- B. Log in to the backup CK and issue the request chassis routing-engine master switch operation command.
- C. Log in to the backup CK and issue the request chassis routing-engine master acquire operation command.
- D. Log in to the backup CK and issue the request iccp-service operation command.

Correct Answer: B

[JN0-347 Practice Test](#)

[JN0-347 Study Guide](#)

[JN0-347 Braindumps](#)