



# JN0-348<sup>Q&As</sup>

Enterprise Routing and Switching, Specialist

## Pass Juniper JN0-348 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-348.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

What are two characteristics of IS-IS CSNPs? (Choose two.)

- A. IS-IS CSNPs contain header information for all link-state PDUs.
- B. IS-IS CSNPs are used to request a copy of a missing link state PDU.
- C. IS-IS CSNPs are used to maintain the link-state database synchronization.
- D. IS-IS CSNPs contain header information for specific requested link-state PDUs.

Correct Answer: AC

---

### QUESTION 2

Which two statements describe NSR? (Choose two.)

- A. NSR requires GRES to function properly.
- B. NSR provides routing loop protection.
- C. NSR rapidly detects link failures.
- D. NSR provides high availability with multiple Routing Engines.

Correct Answer: AD

---

### QUESTION 3

Click the Exhibit button.



```
[edit]
user@router# show interfaces
...
lo0 {
    unit 0 {
        family inet {
            address 1.1.1.1/32;
        }
        family iso {
            address 49.0001.1921.6800.1001.00;
        }
    }
}
```

Which statement is correct about the ISO NET address shown in the exhibit?

- A. The system identifier is 6800.1001.00
- B. The area identifier is 0001
- C. The authority and format identifier (AFI) is 00
- D. This is not a valid NET address

Correct Answer: B

---

#### QUESTION 4

You have configured the router with an IS-IS interface metric of 2048. However, the IS-IS interface metric of 63 is being applied for the interface of this router.

What must you do to enable the larger metric value?

- A. Enable wide metrics.



- B. Disable narrow metrics.
- C. Restart the IS-IS protocol.
- D. Enable level 1 IS-IS routing.

Correct Answer: A

#### QUESTION 5

Click the Exhibit button.

[edit]

```
user@router# run show route protocol aggregate
```

```
inet.0: 9 destinations, 10 routes (9 active, 0 holddown, 0 hidden)
```

```
+ = Active Route, - = Last Active, * = Both
```

```
172.12.16.0/20          *[Aggregate/130] 00:00:32
```

```
Discard
```

Given the route shown in the exhibit, which two prefixes contribute to the aggregate route? (Choose two.)

- A. 172.12.31.0/24
- B. 172.12.33.0/24
- C. 172.12.30.0/24
- D. 172.12.32.0/24

Correct Answer: AC

[Latest JN0-348 Dumps](#)

[JN0-348 VCE Dumps](#)

[JN0-348 Braindumps](#)