



# JN0-351<sup>Q&As</sup>

Enterprise Routing and Switching Specialist (JNCIS-ENT)

**Pass Juniper JN0-351 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-351.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

You have an IBGP neighbor sending you routes. You need to apply a policy so it only evaluates routes being learned from this specific neighbor.

In this scenario, which statement is correct about applying the policy?

- A. The policy should be applied as an export policy to the BGP group level.
- B. The policy should be applied as an import policy to the BGP group level.
- C. The policy should be applied as an export policy to the BGP neighbor level.
- D. The policy should be applied as an import policy to the BGP neighbor level.

Correct Answer: D

---

### QUESTION 2

What is a characteristic of OSPF ASBRs?

- A. ASBRs transmit routing information between the backbone and other areas.
- B. ASBRs cannot be part of the backbone and another area at the same time.
- C. ASBRs inject routing information from outside the OSPF domain.
- D. ASBRs link two OSPF areas.

Correct Answer: C

---

### QUESTION 3

Your router is learning the 172.25.11.0/24 prefix from both the BGP and OSPF protocols. A routing policy is configured on your device to advertise the prefix to an established BGP peer but the peer is not receiving the prefix. You want to allow the prefix to be advertised to the BGP peer.

What should you do on this router to satisfy this requirement?

- A. Enable the automatic removal of peer AS information from the prefix.
- B. Enable the advertisement of inactive BGP routes.
- C. Enable the automatic removal of private AS numbers from the prefix.
- D. Enable the automatic refreshing of BGP routes.

Correct Answer: B

---



#### QUESTION 4

Click the Exhibit button.

```
{master:0} [edit interfaces]
user@switch-1# show
interface-range range-1 {
    member ge-0/0/10;
    member-range ge-0/0/6 to ge-0/0/8;
    unit 0 {
        family ethernet-switching;
    }
}
```

Referring to the exhibit, which set of interfaces is enabled for Ethernet switching?

- A. ge-0/0/6, ge-0/0/7, and ge-0/0/8
- B. ge-0/0/6, ge-0/0/8, and ge-0/0/10
- C. ge0/0/6, ge-0/0/7, ge-0/0/8, and ge-0/0/10
- D. ge-0/0/6 and ge-0/0/8

Correct Answer: C

---

#### QUESTION 5

Click the Exhibit button.



```
default {
    vlan-id 1;
}
v14 {
    vlan-id 14;
    l3-interface irb.14;
}
v15 {
    vlan-id 15;
    l3-interface irb.15;
}
v16 {
    vlan-id 16;
    l3-interface irb.16;
}
```

Referring to the exhibit, the IRB interfaces are configured with which family?

- A. irb
- B. ethernet-switching
- C. inet
- D. l3-interface

Correct Answer: C

[JN0-351 VCE Dumps](#)

[JN0-351 Practice Test](#)

[JN0-351 Braindumps](#)