



# JN0-362<sup>Q&As</sup>

Service Provider Routing and Switching - Specialist (JNCIS-SP)

## Pass Juniper JN0-362 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-362.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Click the Exhibit button.

```
[edit protocols mpls]
user@router# show
label-switched-path R1-to-R6 {
    to 172.17.20.6;
    install 10.3.0.0/24 active;
}

[edit routing-options]
user@router# show
static {
    route 10.3.0.0/24 {
        lsp-next-hop R1-to-R6;
    }
}
```

Both configuration hierarchies shown in the exhibit have been committed to your MX Series device.

Which two statements are true in this scenario? (Choose two.)

- A. Traffic destined to 10.3.0.1 will use the R1-to-R6 LSP as a next hop
- B. Traffic destined to 10.3.0.1 will not use the R1-to-R6 LSP as a next hop
- C. The active 10.3.0.0/24 prefix installed in the route table will have a route preference of 5
- D. The active 10.3.0.0/24 prefix installed in the route table will have a route preference of 7

Correct Answer: AD

---

### QUESTION 2

Click the Exhibit button.



```
[edit interfaces]
user@router# show
ge-0/0/0 {
    unit 0 {
        family inet {
            address 10.1.1.5/31;
        }
        family mpls;
    }
}
ge-0/0/1 {
    unit 0 {
        family inet {
            address 10.1.1.21/31;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.168.0.2/32;
        }
    }
}
```

```
[edit protocols bgp group BGP]
user@router# show
multihop;
local-address 192.168.0.2;
hold-time 30;
family inet {
    unicast;
}
family inet-vpn {
    unicast;
}
family inet6 {
    unicast;
}
family inet6-vpn {
    unicast;
}
family 12vpn {
    signaling;
}
family route-target;
peer-as 65514;
local-as 65514;
neighbor 192.168.0.1;
```



Referring to the exhibit, which two statements are true? (Choose two.)

- A. The configuration is for an external BGP session
- B. The local-address statement is required for the BGP session to establish correctly
- C. The multi-hop statement is required for the BGP session to establish correctly
- D. The configuration is for an internal BGP session

Correct Answer: BD

---

### QUESTION 3

Click the Exhibit button.



```
[edit]
user@R1# show interfaces
ge-0/0/1 {
    unit 0 {
        family inet {
            address 172.18.1.1/30;
        }
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.168.254.1/32;
        }
    }
}

[edit]
user@R1# show routing-options

[edit]
user@R1# show protocols ospf
area 0.0.0.0 {
    interface ge-0/0/1.0;
}

[edit]
user@R2# show interfaces
ge-0/0/1 {
    unit 0 {
        family inet {
            address 172.18.1.2/30;
        }
    }
}

[edit]
user@R2# show routing-options
router-id 192.168.254.1;

[edit]
user@R2# show protocols ospf
area 0.0.0.0 {
    interface ge-0/0/1.0 {
        hello-interval 10;
        dead-interval 40;
    }
}
```



You configured R1 and R2 to form an OSPF adjacency, but the adjacency will not establish. Referring to the exhibit, which statement correctly identifies the problem?

- A. Hello and dead timers are not matching between R1 and R2
- B. R1 does not have a router ID defined
- C. R1 and R2 have the same router ID
- D. R2 has a wrong area configured

Correct Answer: C

Reference: [https://www.juniper.net/documentation/en\\_US/junos/topics/reference/configuration-statement/router-id-edit-routing-options.html](https://www.juniper.net/documentation/en_US/junos/topics/reference/configuration-statement/router-id-edit-routing-options.html)

---

#### QUESTION 4

Which statement about a virtual-router type of routing instance is correct?

- A. It is used to separate large networks into smaller administrative entities
- B. It is the only routing instance type supported on Junos devices
- C. It is used in Layer 3 VPN implementations
- D. It is used to create and maintain separate routing and forwarding tables

Correct Answer: D

---

#### QUESTION 5

You want to disable MAC learning only for interface ge-0/0/0.0 on an MX Series device. Which syntax will accomplish this task?



- A. 

```
switch-options {
    no-mac-learning;
}
```
- B. 

```
bridge-domains {
    bridge-domain-name {
        domain-type bridge;
        interface ge-0/0/0.0;
        bridge-options {
            no-mac-learning;
        }
    }
}
```
- C. 

```
bridge-domains {
    bridge-domain-name {
        domain-type bridge;
        interface ge-0/0/0.0;
        bridge-options {
            interface ge-0/0/0.0 {
                no-mac-learning;
            }
        }
    }
}
```
- D. 

```
switch-options {
    no-mac-learning;
    interface xe-2/0/0.0 {
        no-mac-learning;
    }
}
```



- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: C

Reference: [https://www.juniper.net/documentation/en\\_US/junos/topics/task/configuration/layer-2-servicesmac-bridge-domain-or-logical-interface-disabling-learning-for.html](https://www.juniper.net/documentation/en_US/junos/topics/task/configuration/layer-2-servicesmac-bridge-domain-or-logical-interface-disabling-learning-for.html)

[Latest JN0-362 Dumps](#)

[JN0-362 Study Guide](#)

[JN0-362 Braindumps](#)