# JN0-412 Q&As

Cloud, Specialist (JNCIS-Cloud)

## Pass Juniper JN0-412 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

**https://www.geekcert.com/jn0-412.html**

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper Official Exam Center

- **Instant Download** After Purchase
- **100% Money Back** Guarantee
- **365 Days** Free Update
- **800,000+** Satisfied Customers

**QUESTION 1**

To retrieve attributes of a new virtual machine, with which Contrail component does the OpenStack Nova agent communicate to create a virtual network?

A. Neutron

B. Glance

C. Analytics

D. Control

Correct Answer: A

**QUESTION 2**

What are two predefined tags that are used in Contrail Security policies? (Choose two.)

A. label

B. group

C. family

D. site

Correct Answer: AD

Reference: https://www.juniper.net/documentation/en_US/contrail20/information-products/pathway-pages/ contrail-networking-security-user-guide.pdf

**QUESTION 3**

What are two characteristics of containers used in Contrail? (Choose two.)

A. Each container has the configuration for all applications running in that container.

B. Each pod can contain only one container.

C. Each container has the configuration for all applications running in all containers.

D. Each pod can contain several containers.

Correct Answer: AB

Reference: https://www.juniper.net/documentation/en_US/contrail19/topics/concept/summary-of-containerdesign.html

**QUESTION 4**

You have deployed a Contrail cluster that must support bare-metal servers.

Which protocol is used to communicate between the bare-metal server\\'s virtual tunnel endpoints and the Contrail cluster to establish sessions with the VM servers?

A. SRTP

B. EVPN/VXLAN

C. BGP

D. XMPP

Correct Answer: B

**QUESTION 5**

Click the Exhibit button.

```
{
  BgpPeerInfoData: {
    state_info: {
        last_state: "Idle",
        state: "Idle",
        last_state_at: 1394778927107639
    },
    families: [
        "IPv4:Unicast"
    ],
    peer_type: "external",
    local_asn: 54321,
    configured_families: [
        "inet-vpn"
    ],
    event_info: {
        last_event_at: 1394778927107880,
        last_event: "fsm::EvStart"
    },
    local_id: 181196816,
    send_state: "not advertising",
    peer-address: "10.204.216.253",
    peer-id:181197053,
    hold_tine: 90,
    peer_asn: 12345
  }
}
```


Within your Contrail cluster, a BGP peer is not advertising routes as expected. After issuing the curl http://:8081/analytics/uves/bgp-peers command, you receive the output show in the exhibit.

What is causing this problem?

A. an incorrect local ID

B. an incorrect peer type

C. an incorrect IP address

D. an incorrect family

Correct Answer: D

Latest JN0-412 Dumps JN0-412 PDF Dumps JN0-412 VCE Dumps