



JN0-450^{Q&As}

Mist AI Specialist (JNCIS-MistAI)

Pass Juniper JN0-450 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-450.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Referring to the exhibit, what are two reasons why a Mist AP would have multiple IP addresses? (Choose two.)

Status	
Status	<input checked="" type="checkbox"/> Connected
DHCP Server	10.10.10.1
IP Address (vlan1)	10.10.10.16/24,fe80:0:...
IP Address (vlan100)	10.10.100.22/24,fe80:...
Gateway	10.10.10.1
Primary DNS	8.8.8.8
Secondary DNS	
External IP Address	122.172.108.135
No. Clients	0
Uptime	3h
Last Seen	05:51:36 PM, Mar 27

- A. One IP address is used for control traffic and one address is used for management traffic.
- B. The Local Status Page is enabled in the site settings.
- C. One IP address is used for redundancy.
- D. A guest portal is configured on a tagged VLAN.

Correct Answer: BD

Reference: <https://www.mist.com/documentation/aps-use-ip-addresses/>

QUESTION 2

What are two advantages of lower modulation methods? (Choose two.)



- A. Lower modulation provides higher total aggregate throughput.
- B. Lower modulation provides higher data rates.
- C. Lower modulation is more robust against signal corruption.
- D. Lower modulation can achieve greater range.

Correct Answer: CD

QUESTION 3

Users at a branch site are complaining of a slow performing network and your team suspects the issue may be the new network-attached video camera system. You need to monitor the amount of traffic that a specific device has generated over the past week. In this scenario, where in the Mist dashboard would you accomplish this task?

- A. Clients -> App Clients -> select Client Device
- B. Monitor -> Insights -> select Client Device
- C. Marvis -> type in name of client
- D. Analytics -> Events

Correct Answer: B

Reference: <https://www.mist.com/documentation/checking-the-activity-log-of-a-client/>

QUESTION 4

After setting up a Guest-WLAN using the Mist captive portal, users complain that they are not able to see the captive portal splash page. What would be two reasons for this problem? (Choose two.)

- A. The guest VLAN tag is not configured on the switch port.
- B. The DNS server's IP address is not configured in the IP pool.
- C. The Mist portal IP is not configured under the captive portal bypass.
- D. The RADIUS server is not configured on the WLAN.

Correct Answer: AB

Reference: <https://www.mist.com/documentation/guest-network-doesnt-work/>

QUESTION 5

What is a prerequisite for AP-name generation under auto-provisioning?



- A. The LLDP system name should be configured on the switch ports.
- B. The AP must have the default name of "mist"
- C. The LLDP description should be configured on the switch ports.
- D. The AP must be connected to a Juniper EX Series switch.

Correct Answer: C

Reference: <https://www.mist.com/documentation/auto-provisioning/>

[JN0-450 VCE Dumps](#)

[JN0-450 Study Guide](#)

[JN0-450 Exam Questions](#)