JN0-663 Q&As

Service Provider Routing and Switching, Professional (JNCIP-SP)

Pass Juniper JN0-663 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/jn0-663.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper Official Exam Center

- **Instant Download** After Purchase
- **100% Money Back** Guarantee
- **365 Days** Free Update
- **800,000+** Satisfied Customers

QUESTION 1

Which two statements about IS-IS are correct? (Choose two.)

A. Level 1 intermediate systems exchange routing information with Level 1 intermediate systems on other IS-IS areas.

B. An IS-IS router sets the attached bit in the PDUs it sends to a Level 1 area to indicate that it is a backbone router.

C. A Level 1 router can only form adjacencies with other Level 1 routers.

D. Level 2 routers can form adjacencies with either Level 1 or Level 2 routers.

Correct Answer: BC

QUESTION 2



Referring to the exhibit, what will the IS-IS cost be for R3 to reach R1?

A. 301

B. 73

C. 20

D. 310

Correct Answer: D

QUESTION 3

```
(65001)R1------R2------R3(65001)

[edit]
user@R2# run show route 11.11.11.0/24

inet.0 : 11 destinations, 12 routes (11 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

11.11.11.0/24      *[BGP/170] 00:04:55, localpref 100
                      AS path: 65001 I, validation-state: unverified
                    > to 172.16.1.1 via ge-0/0/0.0
                    [BGP/170] 00:10:33, localpref 100
                      AS path: 65001 65001 I, validation-state: unverified

[edit]
user@R2# show protocols bgp
group R1 {
    neighbor 172.16.1.1 {
        peer-as 65001;
    }
}
group R3 {
    neighbor 172.16.2.1 {
            peer-as 65001;
    }
}
local-as 65002;

[edit]
user@R2# show policy-options
policy-statement lb {
    then {
        load-balance per-packet;
    }
}
policy-statement prepend {
    term 1 {
        then as-path-prepend 65001;
    }
}

[edit]
user@R2# show routing-options
forwarding-table {
    export lb;
}
```

R2 is receiving the same route from R1 and R3. You must ensure that you can load balance traffic for that route.

Referring to the exhibit, which two configuration changes will allow load balancing? (Choose two.)

A. Apply the prepend policy as an import policy under group R1.

B. Configure multipath under the global BGP configuration.

C. Configure multipath under group R1.

D. Apply the prepend policy as an import policy under group R3.

Correct Answer: AB

QUESTION 4

Which statement is correct about BGP FlowSpec between a service provider\\'s PE router and a customer?

A. The flow routes received from a customer are limited to /32 masks for IPv4.

B. The NLRI received from a customer is stored in the flowspec.inet.0 table.

C. The RFC deterministic traffic filtering algorithm is used by default in Junos.

D. The NLRI received from a customer is stored in the inetflow.0 table.

Correct Answer: D

QUESTION 5

```
[edit routing-instances]
user@PE-1# show
vpn=a {
    instance-type vrf;
    interface ge-1/1/4.0;
    route-distinguisher 192.168.1.1:1;
    vrf-target target:65111:101;
    protocols {
        bgp {
            group my-ext-group {
                type external;
                peer-as 65601;
                neighbor 10.0.10.2;
            }
        }
    }
}
```

You have an established Layer 3 VPN between two PE devices. You are asked to only send certain routes from PE-1 over the VPN to the remote site while maintaining all the routes on the PE-1 device. You created a policy that matches the specific routes and then tags these routes with the appropriate target community values.

In this scenario, which configuration changes must be made to satisfy the requirement?

A. Configure the export parameter and apply the policy to the my-ext-group BGP group configuration.

B. Configure the vrf-export parameter and apply the policy under the edit routing-instances vpn-a hierarchy.

C. Configure a RIB group and apply the policy as an import policy to routes distributed into the bgp.13vpn.0 routing table.

D. Configure the import parameter and apply the policy to the my-ext-group BGP group configuration.

Correct Answer: B

JN0-663 PDF Dumps JN0-663 Practice Test JN0-663 Braindumps