



# JN0-681<sup>Q&As</sup>

New Data Center, Professional

**Pass Juniper JN0-681 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-681.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

What are two methods used to scale an IBGP IP Fabric? (Choose two.)

- A. spanning tree
- B. redundant trunk groups
- C. route reflection
- D. confederations

Correct Answer: CD

---

### QUESTION 2

You have configured MP-IBGP to support EVPN for your overlay network. However, you are not seeing the expected routes on your edge devices.



```
Peer: 10.255.14.182+179 AS 69      Local:
10.255.14.176+2131 AS 69
  Type: Internal      State: Established      Flags:
<ImportEval>
  Last State: OpenConfirm      Last Event:
RecvKeepAlive
  Last Error: None
  Options: <Preference LocalAddress HoldTime
GracefulRestart AddressFamily      Rib-group
Refresh>
  Address families configured: inet-vpn-unicast
evpn
  Local Address: 10.255.14.176 Holdtime: 90
Preference: 170
  Number of flaps: 0
  Peer ID: 10.255.14.182      Local ID:
10.255.14.176      Active Holdtime: 90
  Keepalive Interval: 30
  NLRI for restart configured on peer: inet-vpn-
unicast 12vpn
  NLRI advertised by peer: inet-vpn-unicast
12 vpn
  NLRI for this session: inet-vpn-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
```

Referring to the exhibit, how would you solve this problem?

- A. The family evpn signaling parameter must be configured on the remote peer.
- B. Graceful restart must be disabled for this session.
- C. The group types on both devices should be set to external.
- D. The family 12vpn signaling must be configured on the local peer.

Correct Answer: A

### QUESTION 3



You are asked to manage the oversubscription ratio of your spine and leaf IP fabric. You determine that you are at a 3:1 ratio of downstream to upstream traffic and must achieve a 1:1 ratio.

In this scenario, which two actions would you take to achieve this goal? (Choose two.)

- A. Increase the number of server-facing ports that each leaf node uses to carry traffic.
- B. Reduce the number of server-facing ports that each leaf node uses to carry traffic.
- C. Increase the number of spine nodes in your design.
- D. Reduce the number of leaf nodes in your design.

Correct Answer: BC

---

#### QUESTION 4

Which EVPN route type would be used in a DCI situation in which the IP subnets between data centers are completely unique?

- A. Type 2
- B. Type 3
- C. Type 4
- D. Type 5

Correct Answer: D

---

#### QUESTION 5

A client with five data centers spread around the country uses MPLS L2VPNs to provide point-to-point data center interconnects between each data center in a full-mesh network. The client is considering an MPLS EVPN implementation.

In this scenario, what are three advantages of using MPLS EVPN interconnects? (Choose three.)

- A. They provide for static configuration that does not require a Dynamic Routing Protocol.
- B. They provide for lower transmission latency.
- C. They provide for a local proxy ARP/ND resolution.
- D. They provide for point-to-multipoint connectivity.
- E. They provide for MAC learning in the control plane.

Correct Answer: CDE