



# MCD-LEVEL1-DELTA<sup>Q&As</sup>

MuleSoft Certified Developer - Level 1 (Mule 4) DELTA





## Pass Mulesoft MCD-LEVEL1-DELTA Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/mcd-level1-delta.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Mulesoft  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





## QUESTION 1

Refer to the exhibit.

```
#%RAML 1.0
title: Accounts API
version: 1.0

/accounts:
  get:
    description: Get all accounts
    responses:
      200:
        body:
          application/json:
            example:
              id: "48292"
              name: Geordi La Forge
              address: 1 Forge Way, Midgard, CA 95928
              customer_since: "2014-01-04"
              balance: 4829.29
  post:
    description: Create an account
    body:
      application/json:
        example:
          name: Geordi La Forge
          address: 1 Forge Way, Midgard, CA 95928
          customer_since: "2014-01-04"
```

What data is expected by the POST /accounts endpoint?



- A.
- ```
{
  "id": "48292",
  "name": "Geordi La Forge",
  "address": "1 Forge Way, Midgard, CA 95928",
  "customer_since": "2014-01-04",
  "balance": 4829.29
}
```
- B.
- ```
<item>
  <id>48292</id>
  <name>Geordi La Forge</name>
  <address>1 Forge Way, Midgard, CA 95928</address>
  <customer_since>2014-01-04</customer_since>
  <balance>4829.29</balance>
</item>
```
- C.
- ```
<item>
  <name>Geordi La Forge</name>
  <address>1 Forge Way, Midgard, CA 95928</address>
  <customer_since>2014-01-04</customer_since>
  <balance>4829.29</balance>
  <bank_agent_id>48-SJT-282924-KL</bank_agent_id>
</item>
```
- D.
- ```
{
  "name": "Geordi La Forge",
  "address": "1 Forge Way, Midgard, CA 95928",
  "customer_since": "2014-01-04",
  "balance": 4829.29
  "bank_agent_id": "48-SJT-282924-KL"
}
```

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: D

## QUESTION 2

What HTTP method in a RESTful web service is typically used to completely replace an existing resource?

A. GET

B. PATCH

C. POST



D. PUT

Correct Answer: D

### QUESTION 3

A Batch Job scope has three batch steps. An event processor throws an error in the second batch step because the input data is incomplete.

What is the default behavior of the batch job after the error is thrown?

- A. All processing of the batch job stops.
- B. None of these.
- C. Error is ignored.
- D. Event processing continues to the next batch step.

Correct Answer: A

### QUESTION 4

Refer to the exhibits. A web client submits a request to `http://localhost:8081/flights?destination=SFO` and the Web Service Consumer throws a WSC:BAD\_REQUEST error.

What is the next step to fix this error?



```
.....  
Message           : Cannot build default body request for operation [findFlight], the operation requires input  
parameters.  
Error type        : WSC:BAD_REQUEST  
Element           : 10.02.06-soaperrorFlow/processors/0 @ 10.02.06-soaperror:10.02.06-soaperror.xml:21 (Consume)  
Element XML       : <wsc:consume doc:name="Consume" doc:id="49a84a74-2848-4a65-b93f-dcbf59fd4412" config-  
ref="Web_Service_Consumer_Config" operation="findFlight"></wsc:consume>  
.....  
(set debug level logging or '-Dmule.verbose.exceptions=true' for everything)  
.....
```

- A. Set a header In the Consume operation equal to the destination query parameter



- B. set a SOAP payload before the Consume operation that contains the destination query parameter
- C. set a property in the Consume operation equal to the destination query parameter
- D. set a JSON payload before the Consume operation that contains the destination query parameter

Correct Answer: B

#### QUESTION 5

A Utility.dwl file is located in a Mule project at src/main/resources/modules. The Utility.dwl file defines a function named pascalize that reformats strings to pascal case. What is the correct DataWeave to call the pascalize function in a Transform Message component?

- A.

```
⌘dw 2.0
output application/json
import modules.Utility
---
pascalize( "max mule" )
```
- B.

```
⌘dw 2.0
output application/json
import modules::Utility
---
pascalize( "max mule" )
```
- C.

```
⌘dw 2.0
output application/json
import modules::Utility
---
Utility::pascalize( "max mule" )
```
- D.

```
⌘dw 2.0
output application/json
import modules.Utility
---
Utility.pascalize( "max mule" )
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: B



VCE & PDF

GeekCert.com

<https://www.geekcert.com/mcd-level1-delta.html>

2024 Latest geekcert MCD-LEVEL1-DELTA PDF and VCE dumps Download

---

[MCD-LEVEL1-DELTA PDF Dumps](#)

[MCD-LEVEL1-DELTA Practice Test](#)

[MCD-LEVEL1-DELTA Study Guide](#)