



N10-008^{Q&As}

CompTIA Network+

Pass CompTIA N10-008 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/n10-008.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CompTIA
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A network administrator needs to monitor traffic on a specific port on a switch. Which of the following should the administrator configure to accomplish the task?

- A. Port security
- B. Port tagging
- C. Port mirroring
- D. Media access control

Correct Answer: C

QUESTION 2

A company is being acquired by a large corporation. As part of the acquisition process, the company's address should now redirect clients to the corporate organization page. Which of the following DNS records needs to be created?

- A. SOA
- B. NS
- C. CNAME
- D. TXT

Correct Answer: C

CNAME (Canonical Name) is a type of DNS record that maps an alias name to another name, which can be either another alias or the canonical name of a host or domain. A CNAME record can be used to redirect clients from one domain name to another domain name, such as from the company's address to the corporate organization page. SOA (Start of Authority) is a type of DNS record that specifies authoritative information about a DNS zone, such as the primary name server, contact email address, serial number, refresh interval, etc., which does not redirect clients to another domain name. NS (Name Server) is a type of DNS record that specifies which name server is authoritative for a domain or subdomain, which does not redirect clients to another domain name. TXT (Text) is a type of DNS record that provides arbitrary text information about a domain or subdomain, such as SPF (Sender Policy Framework) records or DKIM (DomainKeys Identified Mail) records, which does not redirect clients to another domain name.

QUESTION 3

A network technician is installing a new fiber-optic connection between two buildings on a campus network. When the network technician connects the fiber at the second location, the interface link light does not light up. Which of the following should the technician do NEXT?

- A. Reverse the fiber pair
- B. Check the duplex on each interface
- C. Install a fiber distribution panel



D. Configure a media converter for each switch

Correct Answer: B

QUESTION 4

A server application requires large amounts of data to be sent at a consistent rate. Which of the following should an engineer most likely configure to meet these requirements?

- A. Link speed
- B. Jumbo frames
- C. Switch Virtual Interface
- D. Spanning tree

Correct Answer: B

Jumbo frames are Ethernet frames that have a payload size greater than the standard 1500 bytes. Jumbo frames can carry more data in each frame, which reduces the overhead and improves the throughput and efficiency of data transmission. Jumbo frames are commonly used in storage area networks (SANs), where large amounts of data need to be transferred between servers and storage devices

QUESTION 5

A network administrator is configuring a load balancer for two systems. Which of the following must the administrator configure to ensure connectivity during a failover?

- A. VIP
- B. NAT
- C. APIPA
- D. IPv6 tunneling
- E. Broadcast IP

Correct Answer: A

- Virtual IP (VIP): A virtual IP address should be configured on the load balancer, which is the IP address that clients use to access the load-balanced systems.

[Latest N10-008 Dumps](#)

[N10-008 VCE Dumps](#)

[N10-008 Study Guide](#)