



NS0-181^{Q&As}

NetApp Certified Storage Installation Engineer - ONTAP 9.1

Pass NetApp NS0-181 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-181.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Your customer wants a newly installed AFF C190 cluster to send SNMP notifications to a trap host called OVERWATCH01. In this scenario, which two statements are correct? (Choose two.)

- A. Configure an SNMP community string on the cluster.
- B. Configure DNS on the cluster.
- C. Configure a trap host on the cluster.
- D. Configure a firewall policy and allow SNMP.

Correct Answer: BC

Reference: <http://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-nmg%2FGUID-525CBCFB-E855-4FE6-B975-0AB69F499110.html>

QUESTION 2

You need to install a cluster with a FAS2720 HA pair and a FAS8300 HA pair.

Which NetApp tool will verify which cluster interconnect switches support this configuration?

- A. Active IQ Config Advisor
- B. Interoperability Matrix Tool (IMT)
- C. Hardware Universe (HWU)
- D. mysupport.netapp.com site

Correct Answer: C

Reference: <https://www.netapp.com/media/12424-tr4036.pdf>

QUESTION 3

You are installing a new FAS2750 cluster with 24 HDDs for a customer to run a NAS workload. The customer requests that the HA pair have only a single aggregate that is located on Node 1. Maximum capacity is required. Which action must be performed to ensure that the customer's requests are satisfied?

- A. Perform a takeover of Node 2 to ensure that it does not run.
- B. Assign all data LIFs to Node 1.
- C. Assign all the partitioned disks from Node 2 to Node 1, and create a single aggregate.
- D. Assign all the data partitions from Node 2 to Node 1, and create a single aggregate.

Correct Answer: B



QUESTION 4

In an ONTAP 9.7 cluster, which LIF role is used for sending AutoSupport, establishing Network Time Protocol (NTP), and loading software updates?

- A. cluster management LIF
- B. node management LIF
- C. data LIF
- D. cluster LIF

Correct Answer: B

Reference: <https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-nmg%2FGUID-DFFBE8D9-E824-4085-8FA2-24E367288CB8.html>

QUESTION 5

You are installing a 4-node AFF A400 cluster and are asked to create a custom security message before and after user login. Which two security features are used to perform this task? (Choose two.)

- A. EMS
- B. banner
- C. motd
- D. AutoSupport

Correct Answer: BD

[NS0-181 Practice Test](#)

[NS0-181 Exam Questions](#)

[NS0-181 Braindumps](#)