



NS0-182^{Q&As}

NetApp Certified Storage Installation Engineer, ONTAP

Pass NetApp NS0-182 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-182.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A customer is settings up a new cluster. The customer notices that there are many management ports on the cluster. The customer is know the purpose of the node management network LIF.

What do you tell customer in this scenario?

- A. The node management LIF provides multiple IP address for managing a particular node in the cluster at the hardware level and is used for system maintenance.
- B. The node management LIF is associated with a storage virtual machine (SVM) and is used for communicating with client.
- C. The node management LIF provides a dedicated IP address for the entire cluster and can fail over to any node management or data port in the cluster.
- D. The node management LIF provides a dedicated a IP address to managing a particular node in the cluster and is used for system maintenance.

Correct Answer: D

QUESTION 2

Select the Exhibit tab.

```
cluster::> net int show -fields vserver, data-protocol, lif, role
(network interface show)
vserver  life      role  data protocol
-----  -
CIFS     cifs_lif1  data  cifs
Cluster  cluster1-01_clus1 cluster none
Cluster  cluster1-01_clus2 cluster none
Cluster  cluster1-02_clus1 cluster none
Cluster  cluster1-02_clus2 cluster none
cluster1 cluster1-01_mgmt1 node-mgmt none
cluster1 cluster1-02_mgmt1 node-mgmt none
cluster1 cluster_mgmt cluster-mgmt none
iSCSI    lif1_iscsi data  iscsi
9 entries were displayed
```

Referring to the exhibit, a customer wants to migrate LIF lif1_iscsi to node cluster1-02 port e0d, but they receive an error.

What is the cause of this error?

- A. The LIF is not properly configured.
- B. The designation port is not available.



- C. This type of LIF cannot be migrated.
- D. The LIF does not have a failover group.

Correct Answer: C

QUESTION 3

You need to verify the configuration currently loaded on a Cisco Nexus 3132Q-V cluster switch after applying the RCF.

Which command will accomplish this task?

- A. Use the show bootvar command.
- B. Use the verify config command.
- C. Use the show startup-conf command.
- D. Use the show running-config command

Correct Answer: D

QUESTION 4

A customer has a 6-node AFF A700 cluster and wants to add four nodes without having to update license functionality for each node manually.

In this scenario, which type of license provides this functionality?

- A. Demo License
- B. Site License
- C. Standard License
- D. Evaluation License

Correct Answer: C

QUESTION 5

A customer wants to reduce the task allocation requirement for the root aggregate and increase usable storage by partitioning the disks into one large part and one small part. The small part is used for the root aggregate and the large part for the data aggregates?

In this situation, what is this feature called?

- A. ONTAP
- B. RAID



C. storage virtual machine

D. Advanced Drive Partitioning

Correct Answer: D

Reference: <https://community.netapp.com/t5/Data-ONTAP-Discussions/Feature-in-Netapp/td-p/142416>

[Latest NS0-182 Dumps](#)

[NS0-182 PDF Dumps](#)

[NS0-182 Practice Test](#)