



NS0-184^{Q&As}

NetApp Certified Storage Installation Engineer, ONTAP

Pass NetApp NS0-184 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-184.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Click the Exhibit button.

```
::> event notification destination create -name syslog -syslog 10.10.100.40
::> event notification create -filter-name important-events -destinations syslog
::> cluster log-forwarding create -destination 10.10.100.40 -port 514 -facility user
```

Referring to the exhibit, what information is forwarded to syslog after you enter the scripted install commands? (Choose two.)

- A. command history
- B. EMS messages
- C. AutoSupport messages
- D. SNMP traps

Correct Answer: AC

Reference: <https://www.netapp.com/media/10674-tr4569.pdf>

QUESTION 2

You use the system health subsystem show command to troubleshoot your newly installed ONTAP cluster.

In this scenario, which two health outputs would this command show you? (Choose two.)

- A. data switch cabling
- B. cluster switch cabling
- C. shelf connectivity
- D. node CPU utilization

Correct Answer: CD

Reference: <https://www.doc-developpement-durable.org/file/Projets-informatiques/cours-and-manuelsinformatiques/Netapp/Data%20ONTAP%208.0%207-Mode%20System%20Administration%20Guide.pdf>

QUESTION 3

You have an AFF All SAN Array (ASA) cluster that is running ONTAP 9.7. The cluster is configured for Active Directory domain controller access using a domain tunnel.

In this scenario, which two licenses are enabled on the cluster? (Choose two.)

- A. iSCSI



- B. CIFS
- C. NVMe
- D. FCP

Correct Answer: BD

QUESTION 4

You have just racked a new 6-node switched cluster with ONTAP 9.7. You need to configure the cluster switches.

In this scenario, which two elements would be used to complete the configuration? (Choose two.)

- A. SFP+ port
- B. rlogin
- C. SSH
- D. serial port

Correct Answer: CD

QUESTION 5

A customer has a current AFF ASA A700 cluster and they want to expand the cluster by adding a second AFF ASA A700 HA pair.

In this scenario, which step would be required to accomplish this task?

- A. Install a BES-53248 cluster switch and convert the AFF ASA A700 from a switchless to switch cluster.
- B. Enable ALUA between the two HA pairs to allow cluster backend traffic.
- C. The customer will need to create a separate cluster for the second AFF ASA A700 pair.
- D. Install a Brocade FC switch and create zoning between the original cluster and the new cluster.

Correct Answer: A

[NS0-184 PDF Dumps](#)

[NS0-184 VCE Dumps](#)

[NS0-184 Braindumps](#)