



NS0-184^{Q&As}

NetApp Certified Storage Installation Engineer, ONTAP

Pass NetApp NS0-184 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-184.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You must replace a FAS2750 switchless cluster with an AFF A220 switchless cluster for a customer. The customer requires that you transfer the data from the FAS2750 cluster to the AFF A220.

In this scenario, which two methods would you use to migrate the customer's data? (Choose two.)

- A. Establish an SVM-DR relationship between the two clusters and activate the destination SVM.
- B. Remove all of the HDD drives from the FAS cluster and install them into the AFF cluster.
- C. Install SAS cables between the two clusters and use the vol move command.
- D. Provide cluster switches and build a 4-node cluster, then use the vol move command.

Correct Answer: CD

QUESTION 2

You are installing a new FAS2750 cluster with 24 HDDs for a customer to run a NAS workload. The customer requests that the HA pair have only a single aggregate that is located on Node 1. Maximum capacity is required.

Which action must be performed to ensure that the customer's requests are satisfied?

- A. Perform a takeover of Node 2 to ensure that it does not run.
- B. Assign all data LIFs to Node 1.
- C. Assign all the partitioned disks from Node 2 to Node 1, and create a single aggregate.
- D. Assign all the data partitions from Node 2 to Node 1, and create a single aggregate.

Correct Answer: B

QUESTION 3

In ONTAP 9.7 software, how many different replicated databases (RDBs) exist per node?

- A. 2
- B. 5
- C. 3
- D. 4

Correct Answer: B

Reference: <https://www.storagefreak.net/2017/08/netapp-cdot-ontap-9-rdb-and-cluster-replication-ring>



QUESTION 4

An ONTAP cluster is installed at a secure site. The array has no access to the Internet but is managed 24/7 by onsite engineers. The customer requires that when hardware failures occur, the failures are reported to the NetApp Support team as quickly as possible.

In this scenario, which two tasks should be performed during the project hand-off procedure to satisfy the customer's requirement? (Choose two.)

- A. Ensure that Active IQ Config Advisor is installed.
- B. Ensure that the onsite engineers receive EMS alerts when hardware issues occur.
- C. Educate the onsite engineers about invoking the AutoSupport tool from ONTAP System Manager.
- D. Educate the onsite engineer about how to manually log support calls.

Correct Answer: BC

QUESTION 5

You are installing a new ONTAP 9.7 cluster and attaching the cluster to two separate networks. Your customer has indicated that the same range of client IP addresses are used on both networks and that the networks are never allowed to communicate with each other.

In this scenario, which ONTAP feature must be configured to securely allow all clients to access ONTAP NAS protocols?

- A. BGP
- B. broadcast domains
- C. routing
- D. IPspaces

Correct Answer: B

Reference: <https://www.netapp.com/media/16885-tr-4182.pdf> (9)

[NS0-184 Practice Test](#)

[NS0-184 Study Guide](#)

[NS0-184 Brainsdumps](#)