



# NS0-513<sup>Q&As</sup>

NetApp Certified Implementation Engineer-Data Protection

## Pass Network Appliance NS0-513 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-513.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Network Appliance Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Using SnapCenter 4.0, you are restoring a virtual machine. Which additional tool would be used to monitor the restore?

- A. VMware vSphere Web client
- B. Virtual Storage Console
- C. OnCommand System Manager
- D. OnCommand Unified Manager

Correct Answer: A

---

### QUESTION 2

What are three prerequisites for replicating an Element OS volume to ONTAP? (Choose three.)

- A. SnapMirror must be licensed on the SolidFire cluster.
- B. The ONTAP cluster must be running ONTAP 9.3 or later.
- C. SnapVault must be licensed on the ONTAP cluster.
- D. Enable SnapMirror on the SolidFire cluster.
- E. SnapMirror must be licensed on the ONTAP cluster.

Correct Answer: ADE

Reference: <https://www.netapp.com/us/media/tr-4651.pdf>

---

### QUESTION 3

You create a Snapshot copy of a NetApp volume in either OnCommand System Manager or through the ONTAP CLI.

In this scenario, what happens?

- A. A redirect-on-write Snapshot copy is created and stored within the volume.
- B. A copy-on-write Snapshot copy is created and stored within the volume.
- C. A redirect-on-write Snapshot copy is created and stored within the aggregate.
- D. A copy-on-write Snapshot copy is created and stored within the aggregate.

Correct Answer: B

---

### QUESTION 4



To ensure enough bandwidth for other applications, you want to restrict all replication bandwidth on your destination cluster.

How would you accomplish this task?

- A. Using OnCommand System Manager on your source cluster, create a QoS policy on the source.
- B. Using the ONTAP CLI, enable global throttling on the source cluster.
- C. Using OnCommand System Manager on your destination cluster, create a QoS policy on the destination.
- D. Using the ONTAP CLI, enable global throttling on the destination cluster.

Correct Answer: B

Reference: <https://docs.netapp.com/ontap-9/topic/com.netapp.doc.pow-dap/GUID-BBEDC81C-23CE47FE-A242-F39846A8DD7F.html>

## QUESTION 5

Which two statements are correct about MetroCluster IP requirements for intercluster LIFs? (Choose two.)

- A. At least one interface per node is required.
- B. Either an IPv6 address or IPv4 address is required.
- C. A dedicated network port is required.
- D. Jumbo frames are required.

Correct Answer: BC

[NS0-513 PDF Dumps](#)

[NS0-513 Practice Test](#)

[NS0-513 Braindumps](#)