



# NS0-515<sup>Q&As</sup>

NetApp Certified Implementation Engineer - SAN, E-Series

## Pass NetApp NS0-515 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-515.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





**QUESTION 1**

Click the Exhibit button.

**E2812 and E2824 controller shelf and EF280 flash array:  
Weight**

Unit	Weight		
	Maximum*	Empty**	Shipping***
E2812 controller shelf, with twelve 3.5 in. (8.89 cm) SAS-3 drives each with 6 TB capacity	63.9 lb (29.0 kg)	17.08 (7.75 kg)	80 lb (36.2 kg)
E2824 controller shelf and EF280 flash array, with twenty-four 2.5 in. (6.35) SAS-3 drives each with 900 GB capacity	60.5 lb (27.4 kg)	17.4 lb (7.89 kg)	91 lb (41.2 kg)
<p>* Maximum weight indicates a controller shelf, fully-loaded with the heaviest drives and all other components installed. Because drive weights can vary greatly, this value can vary, depending on the drives installed. Refer to the next table for weight ranges by drive type.</p> <p>** Empty weight indicates a controller shelf with the controller canister, the power fan-canister, and the drives removed.</p> <p>*** Shipping weight indicates the maximum weight of the controller shelf and all shipping material.</p>			

Component	Weight
Controller canister	5.47 lb (2.48 kg)
Power-fan canister	5.2 lb (2.35 kg)
2.5 in. SAS drive	0.6 lb (0.27 kg)
3.5 in. SAS drive	2.09 lb (0.95 kg)
2.5 in. SSD (solid-state disk)	1.33 lb (0.6 kg)

A customer has a raised floor with a weight limit of 700 lb. per floor tile. The customer's data cabinet weights 90 lb. and covers a single floor tile.

Referring to the exhibit, what is the maximum number of E2824 shelves possible to be installed?

- A. 22
- B. 10
- C. 6
- D. 14



Correct Answer: A

---

### QUESTION 2

Which iSCSI setting would you change from its default value to increase the throughput of an iSCSI host port on a NetApp E-Series system?

- A. maximum transmission unit (MTU)
- B. flow control
- C. Challenge-Handshake Authentication Protocol (CHAP)
- D. Time to Live (TTL)

Correct Answer: A

Reference: <https://www.netapp.com/us/media/tr-3409.pdf>

---

### QUESTION 3

An E2812 system, without expansion shelves, is configured with 12 Gb SAS host interface cards (HICs) and is directly connected to a host. However, the host cannot access the volumes.

In this scenario, which two troubleshooting steps should you take? (Choose two.)

- A. Verify that the host can ping the E2812 system over the SAS link
- B. Verify that the E2812 host port SAS link up lights are illuminated
- C. Verify that the E2812 SAS CHAP secret is set
- D. Verify that the correct SAS ports are in use on the E2812 system

Correct Answer: BD

---

### QUESTION 4

An administrator is asked to migrate two DE6600 shelves into a newly deployed E5760 environment that is configured with a stack of two DE460C shelves.

In this scenario, how does the administrator complete this task?

- A. Cable the DE6600s at the beginning of the stack
- B. Cable the DE6600s into a separate stack
- C. Cable the DE6600s at the end of the stack
- D. Cable the DE6600s between the DE460C shelves

Correct Answer: C

---



Reference: [https://library.netapp.com/ecm/ecm\\_download\\_file/ECMLP2773537](https://library.netapp.com/ecm/ecm_download_file/ECMLP2773537)

---

#### QUESTION 5

Which two actions must be performed to enable iSCSI multipathing on Windows for NetApp E-Series systems? (Choose two.)

- A. Set up iSCSI IP addresses on the E-Series system and the Windows host
- B. Install the Host Utilities on the Windows host
- C. Create two VSANs on the iSCSI switches
- D. Install a Host Channel Adapter (HCA) on the Windows host

Correct Answer: AB

[NS0-515 PDF Dumps](#)

[NS0-515 VCE Dumps](#)

[NS0-515 Braindumps](#)