



# NS0-515<sup>Q&As</sup>

NetApp Certified Implementation Engineer - SAN, E-Series

## Pass NetApp NS0-515 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-515.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

The NetApp E-Series system with a 32 Gb FC Host Interface Card (HIC) requires which type of fiber cable to connect to switches or to connect directly to hosts extending up to 100 meters?

- A. OM4
- B. OM3
- C. OM1
- D. OM2

Correct Answer: B

Reference: [https://library.netapp.com/ecm/ecm\\_download\\_file/ECMLP2773537](https://library.netapp.com/ecm/ecm_download_file/ECMLP2773537)

---

### QUESTION 2

In which two locations would you find the WWPNs for a Windows host? (Choose two.)

- A. FC switch
- B. host\\'s BIOS
- C. Windows Device Manager
- D. HBA vendor\\'s utility

Correct Answer: AD

Reference: [https://library.netapp.com/ecm/ecm\\_download\\_file/ECMP1532524](https://library.netapp.com/ecm/ecm_download_file/ECMP1532524) (7)

---

### QUESTION 3

A customer wants to manage an E-Series system over a secure connection between the system and a server. During implementation, you are asked to fulfill this installation requirement.

In this scenario, which three actions are required to complete this task? (Choose three.)

- A. Disable the legacy management interface on the system
- B. Disable all the system\\'s local user roles except admin
- C. Import certificate authority signed certificates into the system
- D. Import the system\\'s self-signed certificates into the system
- E. Complete the certificate signing request on the system

Correct Answer: ADE



#### QUESTION 4

You are setting up asynchronous mirroring between two E2860 systems.

In this scenario, which two prerequisites are required to complete the setup? (Choose two.)

- A. Both the primary and secondary systems must be using the same subnets for mirroring connections.
- B. Both the primary and secondary systems must have the same premium features licensed.
- C. Both systems must be discovered by an Enterprise Management Window (EMW) or SANtricity Unified Manager.
- D. The secondary system must have 2X the storage capacity of the primary system.

Correct Answer: BC

---

#### QUESTION 5

Which NetApp tool provides information on size, weight, acoustic noise, and power of NetApp E-Series systems?

- A. Hardware Universe
- B. Interoperability Matrix Tool
- C. Config Advisor
- D. Active IQ

Correct Answer: A

Reference: [https://library.netapp.com/ecm/ecm\\_download\\_file/ECMLP2773645](https://library.netapp.com/ecm/ecm_download_file/ECMLP2773645)

[NS0-515 VCE Dumps](#)

[NS0-515 Practice Test](#)

[NS0-515 Study Guide](#)