



# NSE4\_FGT-5.6<sup>Q&As</sup>

Fortinet NSE 4 - FortiOS 5.6

## Pass Fortinet NSE4\_FGT-5.6 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

[https://www.geekcert.com/nse4\\_fgt-5-6.html](https://www.geekcert.com/nse4_fgt-5-6.html)

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

What FortiGate feature can be used to prevent a cross-site scripting (XSS) attack? Response:

- A. Web application firewall (WAF)
- B. DoS policies
- C. Rate based IPS signatures
- D. One-arm sniffer

Correct Answer: A

---

### QUESTION 2

Examine the following log message attributes and select two correct statements from the list below.

(Choose two.)

Response:

- A. The category action was set to warning.
- B. The website was allowed on the first attempt.
- C. The user was prompted to decide whether to proceed or go back.
- D. The user failed authentication.

Correct Answer: BC

---

### QUESTION 3

When browsing to an internal web server using a web-mode SSL VPN bookmark, which IP address is used as the source of the HTTP request?

Response:

- A. The FortiGate unit's public IP address
- B. The FortiGate unit's internal IP address
- C. The remote user's virtual IP address
- D. The remote user's public IP address

Correct Answer: B

---



#### QUESTION 4

Which of the following statements are true regarding tunnel mode SSL VPN?

(Choose two.)

Response:

- A. You must be logged into web-only mode SSL VPN to activate tunnel mode.
- B. You need an SSL VPN client (FortiClient) to connect to tunnel mode SSL VPN.
- C. Tunnel mode SSL VPN is configured between two FortiGate devices.
- D. FortiGate will dynamically assign an IP address to the SSL VPN network adapter on the host PC.

Correct Answer: AB

#### QUESTION 5

View the exhibit.

Status	Name	VLAN ID	Type	IP/Netmask
Physical (12)				
	port1		Physical Interface	10.200.1.1 255.255.255.0
	port1-VLAN1	1	VLAN	10.200.5.1 255.255.255.0
	port1-VLAN10	10	VLAN	10.0.10.1 255.255.255.0
	port2		Physical Interface	10.200.2.1 255.255.255.0
	port2-VLAN1	1	VLAN	10.0.5.1 255.255.255.0
	port2-VLAN10	10	VLAN	10.0.20.254 255.255.255.0
	port3		Physical Interface	10.0.1.254 255.255.255.0

Which statements about the exhibit are true?

(Choose two.)

Response:

- A. port1-VLAN10 and port2-VLAN10 can be assigned to different VDOMs.
- B. port1-VLAN1 is the native VLAN for the port1 physical interface.
- C. Traffic between port1-VLAN1 and port2-VLAN1 is allowed by default.
- D. Broadcast traffic received in port1-VLAN10 will not be forwarded to port2-VLAN10.

Correct Answer: AD