



NSE4_FGT-7.0^{Q&As}

Fortinet NSE 4 - FortiOS 7.0

Pass Fortinet NSE4_FGT-7.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/nse4_fgt-7-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

What is the effect of enabling auto-negotiate on the phase 2 configuration of an IPsec tunnel?

- A. FortiGate automatically negotiates different local and remote addresses with the remote peer.
- B. FortiGate automatically negotiates a new security association after the existing security association expires.
- C. FortiGate automatically negotiates different encryption and authentication algorithms with the remote peer.
- D. FortiGate automatically brings up the IPsec tunnel and keeps it up, regardless of activity on the IPsec tunnel.

Correct Answer: D

<https://kb.fortinet.com/kb/documentLink.do?externalID=12069>

QUESTION 2

Which two statements about FortiGate FSSO agentless polling mode are true? (Choose two.)

- A. FortiGate uses the AD server as the collector agent.
- B. FortiGate uses the SMB protocol to read the event viewer logs from the DCs.
- C. FortiGate does not support workstation check.
- D. FortiGate directs the collector agent to use a remote LDAP server.

Correct Answer: BD

Reference: <https://kb.fortinet.com/kb/documentLink.do?externalID=FD47732>

QUESTION 3

By default, FortiGate is configured to use HTTPS when performing live web filtering with FortiGuard servers.

Which CLI command will cause FortiGate to use an unreliable protocol to communicate with FortiGuard servers for live web filtering?

- A. set fortiguard-anycast disable
- B. set webfilter-force-off disable
- C. set webfilter-cache disable
- D. set protocol tcp

Correct Answer: A

Reference: <https://kb.fortinet.com/kb/documentLink.do?externalID=FD48294>



QUESTION 4

Examine the IPS sensor configuration shown in the exhibit, and then answer the question below.

IPS Sensor

Name

WINDOWS_SERVERS

[View IPS Signatures]

Comments

0 / 255

IPS Signatures

+ Add Signatures

Delete

Edit IP Exemptions

Name	Exempt IPs	Severity	Target	Service	OS	Action	Packet Logging
No matching entries found							

IPS Filters

+ Add Filter

Edit Filter

Delete

Filter Details	Action	Packet Logging
Location:server OS:Windows	<div>Block</div>	<div></div>

Apply

Forward Traffic Logs

#	Date/Time	Source	Destination	Application Name	Result	Policy
1	10:09:03	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
2	10:09:03	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
3	10:09:02	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
4	10:09:02	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
5	10:09:01	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
6	10:08:59	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
7	10:08:57	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
8	10:08:57	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
9	10:08:57	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)
10	10:08:57	10.200.1.254	10.200.1.200	HTTPS	✓ 1.30kB/2.65 kB	2(Web-Server-Access-IPS)

An administrator has configured the WINDOWS_SERVERS IPS sensor in an attempt to determine whether the influx of HTTPS traffic is an attack attempt or not. After applying the IPS sensor, FortiGate is still not generating any IPS logs for the HTTPS traffic.

What is a possible reason for this?

- A. The IPS filter is missing the Protocol: HTTPS option.
- B. The HTTPS signatures have not been added to the sensor.



- C. A DoS policy should be used, instead of an IPS sensor.
- D. A DoS policy should be used, instead of an IPS sensor.
- E. The firewall policy is not using a full SSL inspection profile.

Correct Answer: E

QUESTION 5

An administrator observes that the port1 interface cannot be configured with an IP address. What can be the reasons for that? (Choose three.)

- A. The interface has been configured for one-arm sniffer.
- B. The interface is a member of a virtual wire pair.
- C. The operation mode is transparent.
- D. The interface is a member of a zone.
- E. Captive portal is enabled in the interface.

Correct Answer: ABC

https://help.fortinet.com/fos50hlp/54/Content/FortiOS/fortigate-whats-new-54/Top_VirtualWirePair.htm

[Latest NSE4_FGT-7.0 Dumps](#)

[NSE4_FGT-7.0 PDF Dumps](#)

[NSE4_FGT-7.0 Exam Questions](#)