



NSE5_FAZ-5.4^{Q&As}

FortiAnalyzer 5.4 Specialist

Pass Fortinet NSE5_FAZ-5.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/nse5_faz-5-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the purpose of the following CLI command?

```
# configure system global
    set log-checksum md5
end
```

- A. To add the MD5's hash value and authentication code
- B. To encrypt log communications
- C. To add a unique tag to each log to provide that it came from this FortiAnalyzer
- D. To add a log file checksum

Correct Answer: A

QUESTION 2

For proper log correlation between the logging devices and FortiAnalyzer, FortiAnalyzer and all registered devices should:

- A. Use DNS
- B. Use host name resolution
- C. Use an NTP server
- D. Use real-time forwarding

Correct Answer: C

QUESTION 3

How can you configure FortiAnalyzer to permit administrator logins from only specific locations?

- A. Use trusted hosts
- B. Use administrative profiles
- C. Use secure protocols
- D. Use static routes

Correct Answer: A



QUESTION 4

View the exhibit: What does the 1000 MB maximum for disk utilization refer to?

Data Policy

Keep Logs for Analytics	60	Days
Keep Logs for Archive	365	Days

Disk Utilization

Maximum Allowed	1000	MB
Analytics: Archive	70%	30%
Alert and Delete When Usage Reaches	90%	

Out of Available: 62.8 GB
 Modify

- A. The disk quota for each device in the ADOM
- B. The disk quota for the ADOM type
- C. The disk quota for all devices in the ADOM
- D. The disk quota for the FortiAnalyzer model

Correct Answer: A

QUESTION 5

In FortiAnalyzer's FortiView, source and destination IP addresses from FortiGate devices are not resolving to a hostname. How can you resolve the source and destination IPs, without introducing any additional performance impact to FortiAnalyzer?

- A. Configure # set resolve-ip enable in the system FortiView settings
- B. Resolve IPs on FortiGate
- C. Configure local DNS servers on FortiAnalyzer
- D. Resolve IPs on a per-ADOM basis to reduce delay on FortiView while IPs resolve

Correct Answer: A

[Latest NSE5_FAZ-5.4 Dumps](#)

[NSE5_FAZ-5.4 VCE Dumps](#) [NSE5_FAZ-5.4 Braindumps](#)