



NSE7_EFW-6.4^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 6.4

Pass Fortinet NSE7_EFW-6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/nse7_efw-6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

A corporate network allows Internet Access to FSSO users only. The FSSO user student does not have Internet access after successfully logged into the Windows AD network. The output of the `diagnose debug authd fssolist` command does not show student as an active FSSO user. Other FSSO users can access the Internet without problems. What should the administrator check? (Choose two.)

- A. The user student must not be listed in the CA's ignore user list.
- B. The user student must belong to one or more of the monitored user groups.
- C. The student workstation's IP subnet must be listed in the CA's trusted list.
- D. At least one of the student's user groups must be allowed by a FortiGate firewall policy.

Correct Answer: AD

<https://kb.fortinet.com/kb/documentLink.do?externalID=FD38828>

QUESTION 2

View the following FortiGate configuration.

```
config system global
    set snat-route-change disable
end
config router static
    edit 1
        set gateway 10.200.1.254
        set priority 5
        set device "port1"
    next
    edit 2
        set gateway 10.200.2.254
        set priority 10
        set device "port2"
    next
end
```

All traffic to the Internet currently egresses from port1. The exhibit shows partial session information for Internet traffic



from a user on the internal network:

```
# diagnose sys session list
session info: proto=6 proto_state=01 duration=17 expire=7 timeout=3600
flags=00000000 sockflag=00000000 sockport=0 av_idx=0 use=3
ha_id=0 policy_dir=0 tunnel=/
state=may_dirty none app_ntf
statistic(bytes/packets/allow_err): org=57555/7/1 reply=23367/19/1 tuples=2
origin->sink: org pre->post, reply pre->post dev=4->2/2->4
gwy=10.200.1.254/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:64907-
>54.239.158.170:80(10.200.1.1:64907)
hook=pre dir=reply act=dnat 54.239.158.170:80-
>10.200.1.1:64907(10.0.1.10:64907)
pos/(before, after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00000294 tos=ff/ff ips_view=0 app_list=0 app=0
dd_type=0 dd_mode=0
```

If the priority on route ID 1 were changed from 5 to 20, what would happen to traffic matching that user's session?

- A. The session would remain in the session table, and its traffic would still egress from port1.
- B. The session would remain in the session table, but its traffic would now egress from both port1 and port2.
- C. The session would remain in the session table, and its traffic would start to egress from port2.
- D. The session would be deleted, so the client would need to start a new session.

Correct Answer: A

<http://kb.fortinet.com/kb/documentLink.do?externalID=FD40943>

QUESTION 3

Refer to the exhibit, which shows the output of a debug command.



```
FGT # get router info ospf interface port4
port4 is up, line protocol is up
  Internet Address 172.20.121.236/24, Area 0.0.0.0, MTU 1500
  Process ID 0, Router ID 0.0.0.4, Network Type BROADCAST, Cost: 1
  Transmit Delay is 1 sec, State DROther, Priority 1
  Designated Router (ID) 172.20.140.2, Interface Address 172.20.121.2
  Backup Designated Router (ID) 0.0.0.1, Interface Address 172.20.121.239
  Timer intervals configured, Hello 10.000, Dead 40, Wait 40, Retransmit 5
    Hello due in 00:00:05
  Neighbor Count is 4, Adjacent neighbor count is 2
  Crypt Sequence Number is 411
  Hello received 106 send 27, DD received 6 sent 3
  LS-Req received 2 sent 2, LS-Upd received 7 sent 17
  LS-Ack received 4 sent 3, Discarded 1
```

Which two statements about the output are true? (Choose two.)

- A. The local FortiGate OSPF router ID is 0.0.0.4.
- B. Port4 is connected to the OSPF backbone area.
- C. In the network connected to port4, two OSPF routers are down.
- D. The local FortiGate is the backup designated router.

Correct Answer: AB

Area 0.0.0.0 is the backbone area.

QUESTION 4

Examine the output of the `get router info bgp summary` command shown in the exhibit; then answer the question below.



```
# get router info bgp summary
```

```
BGP router identifier 0.0.0.117, local AS number 65117
```

```
BGP table version is 104
```

```
3 BGP AS-PATH entries
```

```
0 BGP community entries
```

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.125.0.60	4	65060	1698	1756	103	0	0	03:02:49	1
10.127.0.75	4	65075	2206	2250	102	0	0	02:45:55	1
10.200.3.1	4	65501	101	115	0	0	0	never	Active

```
Total number of neighbors 3
```

Which statements are true regarding the output in the exhibit? (Choose two.)

- A. BGP state of the peer 10.125.0.60 is Established.
- B. BGP peer 10.200.3.1 has never been down since the BGP counters were cleared.
- C. Local BGP peer has not received an OpenConfirm from 10.200.3.1.
- D. The local BGP peer has received a total of 3 BGP prefixes.

Correct Answer: AC

QUESTION 5

Examine the output from the `\\diagnose debug authd fsso list\\` command; then answer the question below.

```
# diagnose debug authd fsso list --FSSO logons-IP: 192.168.3.1 User: STUDENT Groups: TRAININGAD/
USERS Workstation: INTERNAL2. TRAINING. LAB The IP address 192.168.3.1 is NOT the one used by
the workstation INTERNAL2. TRAINING.
LAB.
```

What should the administrator check?

- A. The IP address recorded in the logon event for the user STUDENT.
- B. The DNS name resolution for the workstation name INTERNAL2. TRAINING. LAB.
- C. The source IP address of the traffic arriving to the FortiGate from the workstation INTERNAL2. TRAINING. LAB.
- D. The reserve DNS lookup for the IP address 192.168.3.1.



Correct Answer: C

[NSE7_EFW-6.4 PDF
Dumps](#)

[NSE7_EFW-6.4 Practice
Test](#)

[NSE7_EFW-6.4
Braindumps](#)