



NSE7_OTS-6.4^{Q&As}

Fortinet NSE 7 - OT Security 6.4

Pass Fortinet NSE7_OTS-6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/nse7_ots-6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You are investigating a series of incidents that occurred in the OT network over past 24 hours in FortiSIEM.

Which three FortiSIEM options can you use to investigate these incidents? (Choose three.)

- A. Security
- B. IPS
- C. List
- D. Risk
- E. Overview

Correct Answer: CDE

QUESTION 2

Refer to the exhibit.

	Name	Type	IP/Netmask	VLAN ID
Physical Interface 14				
	port1	Physical Interface	10.200.1.1/255.255.255.0	
	port1-vlan10	VLAN	10.1.10.1/255.255.255.0	10
	port1-vlan1	VLAN	10.200.5.1/255.255.255.0	1
	port10	Physical Interface	10.0.11.1/255.255.255.0	
	port2	Physical Interface	10.200.2.1/255.255.255.0	
	port2-vlan10	VLAN	10.0.10.1/255.255.255.0	10
	port2-vlan1	VLAN	10.0.5.1/255.255.255.0	1



Which statement about the interfaces shown in the exhibit is true?

- A. port2, port2-vlan10, and port2-vlan1 are part of the software switch interface.
- B. The VLAN ID of port1-vlan1 can be changed to the VLAN ID 10.
- C. port1-vlan10 and port2-vlan10 are part of the same broadcast domain
- D. port1, port1-vlan10, and port1-vlan1 are in different broadcast domains

Correct Answer: D

QUESTION 3

An OT administrator is defining an incident notification policy using FortiSIEM and would like to configure the system with a notification policy. If an incident occurs, the administrator would like to be able to intervene and block an IP address or disable a user in Active Directory from FortiSIEM.

Which step must the administrator take to achieve this task?

- A. Configure a fabric connector with a notification policy on FortiSIEM to connect with FortiGate.
- B. Create a notification policy and define a script/remediation on FortiSIEM.
- C. Define a script/remediation on FortiManager and enable a notification rule on FortiSIEM.
- D. Deploy a mitigation script on Active Directory and create a notification policy on FortiSIEM.

Correct Answer: C

QUESTION 4

An OT network architect needs to secure control area zones with a single network access policy to provision devices to any number of different networks.

On which device can this be accomplished?

- A. FortiGate
- B. FortiEDR
- C. FortiSwitch
- D. FortiNAC

Correct Answer: D

QUESTION 5

An OT architect has deployed a Layer 2 switch in the OT network at Level 1 the Purdue model-process control. The purpose of the Layer 2 switch is to segment traffic between PLC1 and PLC2 with two VLANs. All the traffic between



PLC1 and PLC2 must first flow through the Layer 2 switch and then through the FortiGate device in the Level 2 supervisory control network.

What statement about the traffic between PLC1 and PLC2 is true?

- A. The Layer 2 switch rewrites VLAN tags before sending traffic to the FortiGate device.
- B. The Layer 2 switches routes any traffic to the FortiGate device through an Ethernet link.
- C. PLC1 and PLC2 traffic must flow through the Layer-2 switch trunk link to the FortiGate device.
- D. In order to communicate, PLC1 must be in the same VLAN as PLC2.

Correct Answer: C

[Latest NSE7_OTS-6.4 Dumps](#)

[NSE7_OTS-6.4 PDF Dumps](#)

[NSE7_OTS-6.4 VCE Dumps](#)