



NSE7_SDW-7.0^{Q&As}

Fortinet NSE 7 - SD-WAN 7.0

Pass Fortinet NSE7_SDW-7.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/nse7_sdw-7-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

In which two ways does FortiGate learn the FortiManager IP address or FQDN for zero-touch provisioning? (Choose two.)

- A. From a FortiGuard definitions update
- B. From the central management configuration configured in FortiDeploy
- C. From a DHCP server configured with options 240 or 241
- D. From another FortiGate device in the same local network

Correct Answer: BC

<https://www.historiantech.com/zeroish-touch-provisioning-with-fortimanager-explained/>

QUESTION 2

Refer to the exhibit.

```
FortiGate # diagnose firewall shaper per-ip-shaper list
name FTP_5M
maximum-bandwidth 625 KB/sec
maximum-concurrent-session 5
tos ff/ff
packets dropped 65
bytes dropped 81040
addr=10.1.0.1 status: bps=0 ses=1
addr=10.1.0.100 status: bps=0 ses=1
addr=10.1.10.1 status: bps=1656 ses=3
```

Which two statements about the debug output are correct? (Choose two)

- A. The debug output shows per-IP shaper values and real-time readings.
- B. This traffic shaper drops traffic that exceeds the set limits.
- C. Traffic being controlled by the traffic shaper is under 1 Kbps.
- D. FortiGate provides statistics and reading based on historical traffic logs.

Correct Answer: AB



QUESTION 3

Which three protocols are available only on the command line to configure as performance SLA status check? (Choose three.)

- A. smtp
- B. tcp-echo
- C. twamp
- D. udp-echo
- E. icmp

Correct Answer: BCD

QUESTION 4

Refer to the exhibit.

Name	Role	Default VPN Interface	Protected Subnet
NFGW-1[root]	Hub	port1	SSLVPN_TUNNEL_ADDR1
Spoke-1	Spoke	port1	FABRIC_DEVICE
Spoke-2	Spoke	port1	FIREWALL_AUTH_PORTAL_ADDRESS

What must you configure to enable ADVPN?

- A. On the hub VPN, only the device needs additional phase one sett
- B. ADVPN should only be enabled on unmanaged FortiGate devices.
- C. Each VPN device has a unique pre-shared key configured separately on phase one
- D. The protected subnets should be set to address object to all (0.0.0.0/0)..

Correct Answer: D

SD-WAN 6.4.5 Study Guide. pg 210

QUESTION 5



An administrator is troubleshooting VoIP quality issues that occur when calling external phone numbers. The SD-WAN interface on the edge FortiGate is configured with the default settings, and is using two upstream links. One link has random jitter and latency issues and is based on a wireless connection.

Which two actions must the administrator apply simultaneously on the edge FortiGate to improve VoIP quality using SD-WAN rules?

- A. Select the corresponding SD-WAN balancing strategy in the SD-WAN rule.
- B. Choose the suitable interface based on the interface cost and weight.
- C. Use the performance SLA targets to detect latency and jitter instantly.
- D. Place the troublesome link at the top of the interface preference list.
- E. Configure an SD-WAN rule to load balance all traffic without VoIP.

Correct Answer: AC

[Latest NSE7_SDW-7.0 Dumps](#)

[NSE7_SDW-7.0 PDF Dumps](#)

[NSE7_SDW-7.0 VCE Dumps](#)