



# SPLK-2001<sup>Q&As</sup>

Splunk Certified Developer

## Pass Splunk SPLK-2001 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/splk-2001.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Splunk  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





#### QUESTION 1

Which of the following are requirements for arguments sent to the data/indexes endpoint? (Select all that apply.)

- A. Be url-encoded.
- B. Specify the datatype.
- C. Include the bucket path.
- D. Include the name argument.

Correct Answer: BD

---

#### QUESTION 2

A KV store collection can be associated with a namespace for which of the following users?

- A. Nobody
- B. Users in the admin role.
- C. Users in the admin and power roles.
- D. Users in the admin, power, and splunk-system-user roles.

Correct Answer: B

---

#### QUESTION 3

Which of the following are ways to get a list of search jobs? (Select all that apply.)

- A. Access Activity > Jobs with Splunk Web.
- B. Use Splunk REST to query the /services/search/jobs endpoint.
- C. Use Splunk REST to query the /services/saved/searches endpoint.
- D. Use Splunk REST to query the /services/search/sid/results endpoint.

Correct Answer: AB

Reference: <https://docs.splunk.com/Documentation/Splunk/8.1.2/Search/SupervisejobswiththeJobspage>

---

#### QUESTION 4

The response message from a successful Splunk REST call includes an element. What is contained in an element?

- A. A dictionary of elements.



- B. Metadata encapsulating the element.
- C. A response code indicating success or failure.
- D. An individual element in a collection.

Correct Answer: B

Reference: <https://docs.splunk.com/Documentation/Splunk/8.1.2/RESTUM/RESTusing>

---

#### QUESTION 5

Consider the following Python code snippet used in a Splunk add-on:

```
if not os.path.exists(full_path): self.doAction(full_path, header) else: f = open(full_path) oldORnew = f.readline().split(",")  
f.close()
```

An attacker could create a denial of service by causing an error in either the `open()` or `readline()` commands. What type of vulnerability is this?

- A. CWE-693: Protection Mechanism Failure
- B. CWE-562: Return of Stack Variable Address
- C. CWE-404: Improper Resource Shutdown or Release
- D. CWE-636: Not Failing Securely ('Failing Open')

Correct Answer: C

Reference: <https://dev.splunk.com/enterprise/docs/developapps/testvalidate/securitybestpractices/>

[Latest SPLK-2001 Dumps](#)

[SPLK-2001 PDF Dumps](#)

[SPLK-2001 Practice Test](#)