



# UIPATH-ARDV1<sup>Q&As</sup>

UiPath Advanced RPA Developer v1.0 Exam (UiARD)

## Pass UiPath UIPATH-ARDV1 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/uipath-ardv1.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by UiPath  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

What is the Attach Window activity used for?

- A. To specify the browser container you will be working with
- B. Specifies that you are working with a java window
- C. To specify the top-level window container you will be working with

Correct Answer: C

---

### QUESTION 2

A developer wants to initialize a dictionary with a key of integers and values that are strings. Which initialization expression should be used?

- A. New Dictionary (Of Int32, String) from {{ "3", "5"}, {"three", "five"}}
- B. New Dictionary (Of Int32, String) from {{3, "three"}, {5, "five"}}
- C. New Dictionary (Of Int32, String) from {{ "3", "three"}, {"5", "five"}}
- D. New Dictionary (Of Int32, String) from {{3, 5}, {"three", "five"}}

Correct Answer: B

---

### QUESTION 3

What is the use of attribute when working with selectors?

- A. attribute should not be used according to best practices.
- B. To search through all active window instances for the element matching the top-level tag attributes.
- C. To indicate that attribute is optional in this selector.
- D. To work with selectors that dynamically change the attribute.

Correct Answer: B

Introducing Non-Greedy search in your selectors instructs it to search through all the active windows or browser instances that match the top-level tags of your selector, and not just the window instances in focus. Non-Greedy search makes

use of the idx() attribute, which needs to be included in the top-level tag, as follows:

searches through all active window instances for the element matching the top-level tag attributes.

Please note that the option only searches through window instances in focus.

---



#### QUESTION 4

A developer has created a process that gathers a listing of stock market prices in the following format \_USD ().

How should the third line in RegEx Builder be modified to ensure that only items with prices of at least 100 are identified?

The screenshot shows the RegEx Builder application window. The 'Test Text' field contains the following text:

```
IBM_6738USD (International Business Machines Corporation)  
JNJ_164USD (Johnson & Johnson)  
SPCE_21USD (Virgin Galactic Holdings, Inc.)  
ACB_8USD (Aurora Cannabis Inc.)  
SKLZ_1319USD (Skillz Inc.)  
HAE_70USD (Haemonetics Corporation)
```

The 'RegEx' table is configured as follows:

| RegEx   | Value | Quantifiers                  |
|---------|-------|------------------------------|
| Literal | [A-Z] | Between x and y times (3, 4) |
| Literal | _     | Exactly (1)                  |
| Digit   | \d    | Any (0 or more) (*)          |

The 'Full Expression' field shows the resulting regex: `(?:[A-Z]){3,4}_\d*`. The 'Regex Option' section has ☒ IgnoreCase.

- A. RegEx: One of Value: 123456789 Quantifiers: Between 2 and 4
- B. RegEx: Any word character Value: \w Quantifiers: Exactly 3
- C. RegEx: Digit Value: \d Quantifiers: Exactly 3 (Correct)
- D. RegEx: Literal Value: [0-9] Quantifiers: At least one (1 or more)

Correct Answer: C

Exactly 3 digits would ensure that the price is at least 100 USD, as any price below would have only up to 2 digits.



RegEx Builder

Test Text

IBM\_673\$USD (International Business Machines Corporation)  
JNJ\_164USD (Johnson & Johnson)  
SPCE\_21USD (Virgin Galactic Holdings, Inc.)  
ACB\_BUS\$ (Aurora Cannabis Inc.)  
SKLZ\_13\$9USD (Skillz Inc.)  
HAE\_70USD (Haemonetics Corporation)

| RegEx       | Value | Quantifiers                     |
|-------------|-------|---------------------------------|
| Literal [i] | [A-Z] | Between x and y times 3 4 + - X |
| Literal [i] | -     | Exactly 1 + - X                 |
| Digit [i]   | \d    | Exactly 3 + - X                 |

Full Expression

[?:[A-Z])(3-4) \d(3)

Regex Option

☒ IgnoreCase

Save Cancel

## QUESTION 5

A developer wants to use the output of a Find Children activity to identify a button with a Click activity. Which property of the Click activity must be manually configured during development to identify the button?

- A. ClippingRegion
- B. Element
- C. Selector
- D. WaitForReady

Correct Answer: B

[UIPATH-ARDV1 PDF Dumps](#)

[UIPATH-ARDV1 VCE Dumps](#)

[UIPATH-ARDV1 Braindumps](#)